

IKO GBR 445628 U needle roller bearings

What is the 110 mm D best place to buy 22 mm B IKO GBR 445628 U needle roller bearings online? Manufacturing 60 mm d Service

d	60 mm
D	110 mm
B	22 mm
rs min	1.5 mm
Radial clearance class	C4
Mass	0.78 kg
Dynamic load, C	52.5 kN
Static load, C ₀	36 kN
Fatigue limit load, C _u	1.64 kN
f ₀	14.3
N _{lim} (grease)	3,800 rpm
Min operating temperature, T _{min}	-25 °C
Max operating temperature, T _{max}	110 °C
Characteristic cage frequency, FTF	0.41 Hz
Characteristic rolling element frequency, BSF	5.26 Hz
Characteristic outer ring frequency, BPF ₀	4.08 Hz
Characteristic inner ring frequency, BPFI	5.92 Hz
da min	68 mm
da max	75 mm

Da max	102 mm
ra max	1.5 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.775
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C4-Extra Loose
Inch – Metric	Metric
Long Description	60MM Bore; 110MM Outside Diameter; 22MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No
Other Features	Deep Groove Double Lip Friction Nitrile Rubber Seal -20 To 120 Deg C Prelubricated
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball

Weight / LBS	1.73
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	0.866 Inch 22 Millimeter
Outside Diameter	4.331 Inch 110 Millimeter
Bore	2.362 Inch 60 Millimeter