

IKO KT 15199 needle roller bearings

IKO KT 15199 needle roller bearings Warehouse offers car parts and car accessories. We sell discount online as well as cheap machinery 31.75×35.7×14.3 Size (mm) parts.

Size (mm)	31.75×35.7×14.3
Bore Diameter (mm)	31,75
Outer Diameter (mm)	35,7
Width (mm)	14,3
d	31.75 mm
A	35.7 mm
A1	14.3 mm
A5	30.5 mm
B	42.9 mm
Db1	86.9 mm
Db2	91.1 mm
J	92.1 mm
L	117.5 mm
H	14.3 mm
s1	25.4 mm
T	46 mm
RG – 1/4-28 UNF	1/428 UNF
R1	24 mm
Basic dynamic load rating – C	21.6 kN
Basic static load rating – C0	15.3 kN
Fatigue load limit – Pu	0.655 kN
Limiting speed	3200 r/min

Mass bearing unit	1.85 kg
Thread – G2 – 5/16-24 UNF	5/1624 UNF
Hexagonal key size for grub screw – H	3.969 mm
Housing material	Stainless steel
N	14.3 mm
RG	1/4-28 UNF
Basic dynamic load rating C	21.6 kN
Basic static load rating C0	15.3 kN
Fatigue load limit Pu	0.655 kN
Thread grub screw G2	5/16-24 UNF
Hexagonal key size for grub screw N	3.969 mm
Recommended tightening torque for grub screw	6.5 N·m
Recommended diameter for attachment bolts, mm G	12 mm
Recommended diameter for attachment bolts, inch G	0.5 in
Housing	FYWR 507 Y
Bearing	YAR 207-104-2RFGR/HV
End cover	ECW 207