

IKO KT 222617 needle roller bearings

We 70 Outer Diameter (mm) Provide Extensive IKO KT 222617 needle roller bearings Selection And 125x70x31 Size (mm) Competitive Wholesale 125 Bore Diameter (mm) Pricing.

Size (mm)	125x70x31
Bore Diameter (mm)	125
Outer Diameter (mm)	70
Width (mm)	31
d	70 mm
D	125 mm
B	31 mm
d2	83 mm
D1	111 mm
b	6 mm
K	3 mm
r1,2 – min.	1.5 mm
da – min.	79 mm
Da – max.	116 mm
ra – max.	1.5 mm
Basic dynamic load rating – C	213 kN
Basic static load rating – C0	228 kN
Fatigue load limit – Pu	25.5 kN
Reference speed	5000 r/min
Limiting speed	6700 r/min
Calculation factor – e	0.23
Calculation factor – Y1	2.9

Calculation factor – Y2	4.4
Calculation factor – Y0	2.8
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	1.651
EAN	7316576652356
Product Group	B04311
Internal Clearance	C0-Medium
Mounting Method	Shaft Mount
Rolling Element	Spherical Roller Bearing
Bore Profile	Straight
Cage Material	Steel
Enclosure	Open
Number of Rows of Rollers	Double Row
Relubricatable	Yes
Withdrawal Sleeve	Not Applicable
Withdrawal Nut	Not Applicable
Inch – Metric	Metric
Long Description	70MM Straight Bore; 125MM Outside Diameter; 31MM Width; C0-Medium Clearance; Shaft Mount; Double Row
UNSPSC	31171510
Harmonized Tariff Code	84823080
Noun	Bearing
Keyword String	Spherical
Weight / LBS	3.637
Width	1.22 Inch 31 Millimeter
Outside Diameter	4.921 Inch 125 Millimeter

Bore	2.756 Inch 70 Millimeter
Adapter Part Number	Not Applicable Inch Not Applicable Millimeter
bore diameter:	70 mm
maximum rpm:	6700 RPM
outside diameter:	125 mm
operating temperature range:	Maximum of +390 °F
overall width:	31 mm
cage material:	Steel
bore type:	Straight
bearing material:	Steel
outer ring type:	Not Split
precision rating:	Not Rated
internal clearance:	C0
finish/coating:	Uncoated
closure type:	Open
outer ring width:	31 mm
lubrication hole type:	Lubrication Groove & Hole
fillet radius:	1.5 mm
dynamic load capacity:	208 kN
series:	222
static load capacity:	228 kN
d2 ≈	83 mm
D1 ≈	111 mm
r1,2 min.	1.5 mm
da min.	79 mm
Da max.	116 mm
ra max.	1.5 mm
Basic dynamic load rating C	213 kN

Basic static load rating C0	228 kN
Fatigue load limit Pu	25.5 kN
Calculation factor e	0.23
Calculation factor Y1	2.9
Calculation factor Y2	4.4
Calculation factor Y0	2.8
Mass bearing	1.55 kg