

IKO KTV 91214 EG needle roller bearings

IKO KTV 91214 EG needle roller bearings Engineering Calculator 41,275 Bore Diameter (mm) , Manufacturing Service . Get Your 41.275×76.2×22.225 Size (mm) Free.

Size (mm)	41.275×76.2×22.225
Bore Diameter (mm)	41,275
Outer Diameter (mm)	76,2
Width (mm)	22,225
d	41,275 mm
D	76,2 mm
T	22,225 mm
B	23,02 mm
C	17,462 mm
ra1 max.	0,8 mm
a	17 mm
r min.	3,5 mm
r1 min.	0,8 mm
Da	68 mm
db	47,5 mm
ra max.	3,5 mm
da	53 mm
Db	72 mm
Weight	0,429 Kg
Basic dynamic load rating (C)	66 kN
Basic static load rating (C0)	82 kN
(Grease) Lubrication Speed	4800 r/min

(Oil) Lubrication Speed	6700 r/min
Calculation factor (e)	0,39
Calculation factor (Y0)	0,84
LangID	1
ALP23	0
outer r	0.8
ALP22	18
D_	76.2
ALP21	29
SHOG_yobi	24780R/24720R
RAr	138.739
inner r	3.5
GRS rpm	4800
D_b	72
D_a	68
DE_	65.495
SLR	16
Prod_Type3	TRBSR_ID_A
BETA_	1
ALPHA_	14.65
SDM_	58.004
DA1	8.877
DA2	7.857
hidYobi	24780/24720
Y1	1.5
B_	23.02
Oil rpm	6700
hidTable	ecat_NSTPRI
Y0	0.84

inner ra	3.5
outer rb	0.8
C0	82
CUP	0.15
e	0.39
DA_	8.37
BET21	3
BET22	40
BET23	0
Z_	18
C_	17.462
yobi	24780/24720
KBRG	3161
CONE	0.279
DI_	49.757