IKO NA 4918U needle roller bearings

Welcome to the 1.1875 in d 3.2500 in inner ring width: IKO NA 4918U needle roller bearings online seller.

d1.1875 ininner ring width:3.2500 inD4.5938 inbearing material:52290 Steel/Black 0xideB3.2500 inseal type:High Performance Sealbore type:Roundlength through bore:3.2500 induty type:Standard Dutyoperating temperature range:Max 220°mounting type:Two-Bolt Flangefinish/coating:Uncoatedhousing material:Stainless Steelbolt size:.4375 inlocking device:Skwezloc Collarlubrication type:Lubrication Fittingexpansion type:CRFTS-PN-Thousing width:1.2188 inreplacement bearing:PN-19Tmanufacturer catalog number:708251		1
D4.5938 inbearing material:52290 Steel/Black OxideB3.2500 inseal type:High Performance Sealbore type:Roundlength through bore:3.2500 induty type:Standard Dutyoperating temperature range:Max 220°mounting type:Two-Bolt Flangefinish/coating:Uncoatedhousing material:Stainless Steelbolt size:.4375 inlocking device:Skwezloc Collarlubrication type:Lubrication Fittingexpansion type:Ron-Expansion Bearing (Fixed)series:CRFTS-PN-Thousing width:1.2188 inreplacement bearing:PN-19T	d	1.1875 in
bearing material:52290 Steel/Black OxideB3.2500 inseal type:High Performance Sealbore type:Roundlength through bore:3.2500 induty type:Standard Dutyoperating temperature range:Max 220°mounting type:Two-Bolt Flangefinish/coating:Uncoatedhousing material:Stainless Steelbolt size:.4375 inlocking device:Skwezloc Collarlubrication type:Non-Expansion Bearing (Fixed)series:CRFTS-PN-Thousing width:1.2188 inreplacement bearing:PN-19T	inner ring width:	3.2500 in
B3.2500 inseal type:High Performance Sealbore type:Roundlength through bore:3.2500 induty type:Standard Dutyoperating temperature range:Max 220°mounting type:Two-Bolt Flangefinish/coating:Uncoatedhousing material:Stainless Steelbolt size:.4375 inlocking device:Skwezloc Collarlubrication type:Non-Expansion Bearing (Fixed)series:CRFTS-PN-Thousing width:1.2188 inreplacement bearing:PN-19T	D	4.5938 in
seal type:High Performance Sealbore type:Roundlength through bore:3.2500 induty type:Standard Dutyoperating temperature range:Max 220°mounting type:Two-Bolt Flangefinish/coating:Uncoatedhousing material:Stainless Steelbolt size:.4375 inlocking device:Skwezloc Collarlubrication type:Non-Expansion Bearing (Fixed)series:CRFTS-PN-Thousing width:1.2188 inreplacement bearing:PN-19T	bearing material:	52290 Steel/Black Oxide
bore type:Roundlength through bore:3.2500 induty type:Standard Dutyoperating temperature range:Max 220°mounting type:Two-Bolt Flangefinish/coating:Uncoatedhousing material:Stainless Steelbolt size:.4375 inlocking device:Skwezloc Collarlubrication type:Lubrication Fittingexpansion type:Roundfinish:1.2188 inreplacement bearing:PN-19T	В	3.2500 in
lengththrough bore:3.2500 induty type:Standard Dutyoperating temperature range:Max 220°mounting type:Two-Bolt Flangefinish/coating:Uncoatedhousing material:Stainless Steelbolt size:.4375 inlocking device:Skwezloc Collarlubrication type:Non-Expansion Bearing (Fixed)series:CRFTS-PN-Thousing width:1.2188 inreplacement bearing:PN-19T	seal type:	High Performance Seal
duty type:Standard Dutyoperating temperature range:Max 220°mounting type:Two-Bolt Flangefinish/coating:Uncoatedhousing material:Stainless Steelbolt size:.4375 inlocking device:Skwezloc Collarlubrication type:Lubrication Fittingexpansion type:Non-Expansion Bearing (Fixed)series:CRFTS-PN-Thousing width:1.2188 inreplacement bearing:PN-19T	bore type:	Round
operating temperature range:Max 220°mounting type:Two-Bolt Flangefinish/coating:Uncoatedhousing material:Stainless Steelbolt size:.4375 inlocking device:Skwezloc Collarlubrication type:Lubrication Fittingexpansion type:Non-Expansion Bearing (Fixed)series:CRFTS-PN-Thousing width:1.2188 inreplacement bearing:PN-19T	length through bore:	3.2500 in
mounting type:Two-Bolt Flangefinish/coating:Uncoatedhousing material:Stainless Steelbolt size:.4375 inlocking device:Skwezloc Collarlubrication type:Lubrication Fittingexpansion type:Non-Expansion Bearing (Fixed)series:CRFTS-PN-Thousing width:1.2188 inreplacement bearing:PN-19T	duty type:	Standard Duty
finish/coating: Uncoated housing material: Stainless Steel bolt size: .4375 in locking device: Skwezloc Collar lubrication type: Lubrication Fitting expansion type: Non-Expansion Bearing (Fixed) series: CRFTS-PN-T housing width: 1.2188 in replacement bearing: PN-19T	operating temperature range:	Max 220°
housing material:Stainless Steelbolt size:.4375 inlocking device:Skwezloc Collarlubrication type:Lubrication Fittingexpansion type:Non-Expansion Bearing (Fixed)series:CRFTS-PN-Thousing width:1.2188 inreplacement bearing:PN-19T	mounting type:	Two-Bolt Flange
bolt size:.4375 inlocking device:Skwezloc Collarlubrication type:Lubrication Fittingexpansion type:Non-Expansion Bearing (Fixed)series:CRFTS-PN-Thousing width:1.2188 inreplacement bearing:PN-19T	finish/coating:	Uncoated
locking device:Skwezloc Collarlubrication type:Lubrication Fittingexpansion type:Non-Expansion Bearing (Fixed)series:CRFTS-PN-Thousing width:1.2188 inreplacement bearing:PN-19T	housing material:	Stainless Steel
lubrication type:Lubrication Fittingexpansion type:Non-Expansion Bearing (Fixed)series:CRFTS-PN-Thousing width:1.2188 inreplacement bearing:PN-19T	bolt size:	.4375 in
expansion type:Non-Expansion Bearing (Fixed)series:CRFTS-PN-Thousing width:1.2188 inreplacement bearing:PN-19T	locking device:	Skwezloc Collar
series: CRFTS-PN-T housing width: 1.2188 in replacement bearing: PN-19T	lubrication type:	Lubrication Fitting
housing width: 1.2188 in replacement bearing: PN-19T	expansion type:	Non-Expansion Bearing (Fixed)
replacement bearing: PN-19T	series:	CRFTS-PN-T
	housing width:	1.2188 in
manufacturer catalog number: 708251	replacement bearing:	PN-19T
	manufacturer catalog number:	708251