

IKO NA 6913UU needle roller bearings

With over 10170 full-service stores, 63.5 mm d our IKO NA 6913UU needle roller bearings inventory is extensive and our parts are priced right. within 24 hours. This helps you maximize your productivity by saving time and your 29.01 mm B hard-earned dollars.

d	63.5 mm
B	29.01 mm
d1	93 mm
e	0.38
Y2	1.56
Y0	0.86
Dynamic load, C	128 kN
Rating life coefficient, A2	1.4
Static load, C0	177 kN
Fatigue limit load, Cu	21.6 kN
Nlim (oil)	4,000 rpm
Nlim (grease)	3,000 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.44 Hz
Characteristic rolling element frequency, BSF	7.91 Hz
Characteristic outer ring frequency, BPF0	9.23 Hz

Characteristic inner ring frequency, BPFI	11.77 Hz
ra max	3.5 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
UNSPSC	31171527
Weight / Kilogram	0.989
EAN	4547359534375
Product Group	B04334
Precision Class	Standard
Component	Cone
Basic Number	483
Number of Tapered Rows	Single Row
Inch – Metric	Inch
Long Description	Cone; Standard Precision; 483 Basic Number; 2-1/2" Bore; 1.142" Width; Single Row of Rolle
Outside Diameter	0 Inch 0 Millimeter
Flange Outside Diameter	0 Inch 0 Millimeter
Bore	2.5 Inch 63.5 Millimeter
Width	1.142 Inch 29.007 Millimeter