

# IKO NAG 4910UU cylindrical roller bearings

Enjoy High Margins on Competitive Pricing.Great Wholesale Products at 1150x710x345 Size (mm) 1150 Bore Diameter (mm) 710 Outer Diameter (mm) Low Costs.

Size (mm)	1150x710x345
Bore Diameter (mm)	1150
Outer Diameter (mm)	710
Width (mm)	345
d	710 mm
D	1150 mm
B	345 mm
d2	851 mm
D1	1017 mm
b	22.3 mm
K	12 mm
r1,2 – min.	9.5 mm
da – min.	750 mm
Da – max.	1110 mm
ra – max.	8 mm
Basic dynamic load rating – C	14732 kN
Basic static load rating – C0	26000 kN
Fatigue load limit – Pu	1530 kN
Reference speed	240 r/min
Limiting speed	450 r/min
Calculation factor – e	0.28
Calculation factor – Y1	2.4

Calculation factor – Y2	3.6
Calculation factor – Y0	2.5
d2 ≈	851 mm
D1 ≈	1017 mm
r1,2 min.	9.5 mm
da min.	750 mm
Da max.	1110 mm
ra max.	8 mm
Basic dynamic load rating C	14732 kN
Basic static load rating C0	26000 kN
Fatigue load limit Pu	1530 kN
Calculation factor e	0.28
Calculation factor Y1	2.4
Calculation factor Y2	3.6
Calculation factor Y0	2.5
Mass bearing	1450 kg