

# IKO NAG 4918UU cylindrical roller bearings

Online IKO NAG 4918UU cylindrical roller bearings Expert. More Choices. IKO NAG 4918UU cylindrical roller bearings in Stock & Ready to Ship Now! 110x170x45 Size (mm) 110 Bore Diameter (mm)

Size (mm)	110x170x45
Bore Diameter (mm)	110
Outer Diameter (mm)	170
Width (mm)	45
d	110 mm
D	170 mm
B	45 mm
C	45 mm
r min.	2 mm
da min.	120 mm
da max	124 mm
Da min	153 mm
Da max.	160 mm
ra max.	2 mm
Weight	3,76 Kg
Basic dynamic load rating (C)	293 kN
Basic static load rating (C0)	465 kN
(Grease) Lubrication Speed	2000 r/min
(Oil) Lubrication Speed	2400 r/min
Calculation factor (e)	0,24
Calculation factor (Y0)	2,8
Calculation factor (Y2)	4,2

Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A
Weight / Kilogram	3.8
EAN	0029176008610
Product Group	B04311
Internal Clearance	C0-Medium
Mounting Method	Shaft Mount
Rolling Element	Spherical Roller Bearing
Bore Profile	Straight
Cage Material	Steel
Enclosure	Open
Number of Rows of Rollers	Double Row
Relubricatable	Yes
Withdrawal Sleeve	Not Applicable
Inch – Metric	Metric
Long Description	110MM Straight Bore; 170MM Outside Diameter; 45MM Width; C0-Medium Clearance; Shaft Mount; Double Ro
UNSPSC	31171510
Harmonized Tariff Code	84823080
Noun	Bearing
Keyword String	Spherical
Manufacturer Item Number	23022CDE4
Weight / LBS	3.8
Outside Diameter	6.693 Inch   170 Millimeter
Bore	4.331 Inch   110 Millimeter
Width	1.772 Inch   45 Millimeter

Adapter Part Number	Not Applicable Inch   Not Applicable Millimeter
Y3	2.8
hidYobi	23022CDE4
LangID	1
Y1	2.8
D_	170
Y2	4.2
Macha rpm	0
B_	45
da min	120
hidTable	ecat_NSSPHR
Oil rpm	2400
Y0	2.8
mass	3.76
GRS rpm	2000
ra	2
TSR rpm	3200
C0	465
DE_	156.055
X0	1
Prod_Type3	SRB_CTB_CB
X1	1
X2	0.67
SIR	17
e	0.24
DA_	15
bomp	23022CDE4
Z_	25

ALP2	0
ALP1	9
ALP3	0
D_a max	160
D_a min	153
yobi	23022CDE4
ALPHA_	0.157
SDM_	141.239
r	2
KBRG	2321
SBRG	30
DI_	126.424