

# IKO NAS 5084UU cylindrical roller bearings

Online IKO NAS 5084UU cylindrical roller bearings Expert. More Choices. IKO NAS 5084UU cylindrical roller bearings in Stock 0.0 Inventory & Ready to Ship Now!

|                            |               |
|----------------------------|---------------|
| Inventory                  | 0.0           |
| Manufacturer Name          | TIMKEN        |
| Minimum Buy Quantity       | N/A           |
| EAN                        | 0883450505680 |
| Weight / US pound          | 0.01          |
| Product Group              | M06110        |
| Shaft Size                 | 3.1875 in     |
| Shaft Size Type            | Imperial      |
| Weight                     | 46.0 lb       |
| UPC Code                   | 0883450505680 |
| Type E Open Cover Number   | EUDR-3 3/16   |
| Type E Closed Cover Number | EUC-H         |
| Dimension B                | 5 in          |
| Dimension L                | 14 in         |
| Dimension A                | 3-1/2 in      |
| Dimension J Min.           | 10-13/16 in   |
| Dimension J Max.           | 11-3/16 in    |
| Bolt Diameter              | 7/8 in        |
| Dimension N                | 1 in          |
| Dimension N1               | 1-3/16 in     |
| Dimension H1               | 2-1/4 in      |
| Dimension H2               | 7-1/2 in      |

|  |   |
|--|---|
| Dimension d1   | 5-17/32 in  |
| Dimension H  | 3-3/4 in  |
| Dimension Ac   | 6 in  |
| Dimension d2   | 6.7 in  |
| e  | 0.50  |
| X (if $F_a/F_r \leq e$ )                                   | 0.87  |
| Y (if $F_a/F_r \leq e$ )                                   | 1.71  |
| X (if $F_a/F_r > e$ )                                      | 0.7   |
| Y (if $F_a/F_r > e$ )                                      | 2.07  |
| K Factor   | 1.19  |
| C90 Dynamic Load Rating <sup>1</sup>                       | 19600 lb  |
| C0 Static Load Rating                                      | 108600 lb   |
| Fa-max Maximum Permissible Thrust Load <sup>2</sup>        | 5181 lb   |
| Fr-max Maximum Allowable Slip Fit Radial Load <sup>3</sup> | 16000 lb  |
| Max. Speed <sup>4</sup>                                    | 1640 rpm  |
| Note   | Note: All units have a 1/8 pipe thread grease fitting<br>The Maximum Permissible Thrust Load applies to |