## IKO NTB 1730 needle roller bearings

Various 3700 Series types and sizes to accommodate your IKO NTB 1730 needle roller bearings requirements.

| Series  | 3700          |
|---|---------------|
| Cone Part Number  | 3777          |
| Design Units  | Imperial      |
| Cage Type   | Stamped Steel |
| C1 — Dynamic Radial Rating (Two-Row, 1 million revolutions)1      | 47800 lbf     |
| C90(2) — Dynamic Radial Rating (Two-Row, 90 million revolutions)2 | 12400 lbf     |
| d   | 1.8125 in     |
| B — Cone Width  | 1.1930 in     |
| R — Cone Backface To Clear Radius3                                | 0.14 in       |
| da — Cone Frontface Backing Diameter                              | 2.09 in       |
| db — Cone Backface Backing Diameter                               | 2.36 in       |
| Ab – Cage-Cone Frontface Clearance                                | 0.06 in       |
| Aa – Cage-Cone Backface Clearance                                 | 0.06 in       |
| a — Effective Center Location4                                    | -0.32 in      |
| C90 – Dynamic Radial Rating (90 million revolutions)5             | 7120 lbf      |
| C1 — Dynamic Radial Rating (1 million revolutions)6               | 27500 lbf     |
| C0 — Static Radial Rating   | 34300 lbf     |
| Ca90 — Dynamic Thrust Rating (90 million<br>revolutions)7         | 4120 lbf      |
| K – Factor8   | 1.73          |

| G1 — Heat Generation Factor (Roller-Raceway) | 49.9   |
|--|--------|
| G2 — Heat Generation Factor (Rib-Roller End) | 14.5   |
| Cg – Geometry Factor                         | 0.0903 |