IKO PHS 5 plain bearings

How do I place an EMERGENCY order for a IKO PHS 5 plain bearings 32 mm A that I want to pick up at a our store?

A 32 mm A1 12 mm A2 24 mm B 34 mm A5 19.7 mm d 25.4 mm Dz 60 mm G M6x1 H 89 mm H1 76 mm H2 51 mm L 97 mm L1 62 mm L2 10 mm NN 19mm NN 19mm NN 19mm NN 19mm NN 19mm S1 17 mm S 14.3 mm SW 3.18 mm Z 47.5 mm C 14 kN		
A2	Α	32 mm
B 34 mm A5 19.7 mm d 25.4 mm Dz 60 mm G M6x1 H 89 mm H1 76 mm H2 51 mm L 97 mm L1 62 mm L2 10 mm L3 51 mm N 19mm NN 19mm NN 19mm NN 19mm NN 19mm S 32 mm P 150 mm S 14.3 mm SW 3.18 mm Z 47.5 mm	A1	12 mm
A5 19.7 mm d 25.4 mm Dz 60 mm G M6x1 H 89 mm H1 76 mm H2 51 mm L 97 mm L1 62 mm L2 10 mm L3 51 mm N 19mm N 19mm N1 16 mm N2 32 mm P 150 mm S 14.3 mm SW 3.18 mm Z 47.5 mm	A2	24 mm
d 25.4 mm Dz 60 mm G M6x1 H 89 mm H1 76 mm H2 51 mm L 97 mm L1 62 mm L2 10 mm L3 51 mm N 19mm N1 16 mm N2 32 mm P 150 mm S1 17 mm S 14.3 mm SW 3.18 mm Z 47.5 mm	В	34 mm
Dz 60 mm G M6x1 H 89 mm H1 76 mm H2 51 mm L 97 mm L1 62 mm L2 10 mm L3 51 mm N 19mm N1 16 mm N2 32 mm P 150 mm s1 17 mm S 14.3 mm SW 3.18 mm Z 47.5 mm	A5	19.7 mm
G M6×1 H 89 mm H1 76 mm H2 51 mm L 97 mm L1 62 mm L2 10 mm L3 51 mm N 19mm N1 16 mm N2 32 mm P 150 mm s1 17 mm S 14.3 mm SW 3.18 mm Z 47.5 mm	d	25.4 mm
H H1 F1 H1 F2 H2 F1	Dz	60 mm
H1 76 mm H2 51 mm L 97 mm L1 62 mm L2 10 mm L3 51 mm N 19mm N1 16 mm N2 32 mm P 150 mm s1 17 mm S 14.3 mm SW 3.18 mm Z 47.5 mm	G	M6×1
H2 51 mm L 97 mm L1 62 mm L2 10 mm L3 51 mm N 19mm N1 16 mm N2 32 mm P 150 mm s1 17 mm S 14.3 mm SW 3.18 mm Z 47.5 mm	Н	89 mm
L 97 mm L1 62 mm L2 10 mm L3 51 mm N 19mm N1 16 mm N2 32 mm P 150 mm s1 17 mm S 14.3 mm SW 3.18 mm Z 47.5 mm	H1	76 mm
L1 62 mm L2 10 mm L3 51 mm N 19mm N1 16 mm N2 32 mm P 150 mm s1 17 mm S 14.3 mm SW 3.18 mm Z 47.5 mm	H2	51 mm
L2	L	97 mm
L3 51 mm N 19mm N1 16 mm N2 32 mm P 150 mm s1 17 mm S 14.3 mm SW 3.18 mm Z 47.5 mm	L1	62 mm
N 19mm N1 16 mm N2 32 mm P 150 mm s1 17 mm S 14.3 mm SW 3.18 mm Z 47.5 mm	L2	10 mm
N1 16 mm N2 32 mm P 150 mm s1 17 mm S 14.3 mm SW 3.18 mm Z 47.5 mm	L3	51 mm
N2 32 mm P 150 mm s1 17 mm S 14.3 mm SW 3.18 mm Z 47.5 mm	N	19mm
P 150 mm 17 mm 17 mm 17 mm 14.3 mm 18 mm 17 mm 17 mm 18 mm 1	N1	16 mm
\$1 17 mm \$ 14.3 mm \$ 3.18 mm \$ 47.5 mm	N2	32 mm
S 14.3 mm SW 3.18 mm Z 47.5 mm	P	150 mm
SW 3.18 mm Z 47.5 mm	s1	17 mm
Z 47.5 mm	S	14.3 mm
	SW	3.18 mm
C 14 kN	Z	47.5 mm
	С	14 kN

C0	7.88 kN
T min.	-20 °C
T max.	100 °C
Weight	0.87 kg
Recommended tightening torque for set screw	3.7 Nm
Designation of housing	T205N-
Designation of bearing	UC205 - 16G2L4
Designation of closed end cover	SCC205
Designation of open end cover	SC0U205-16