

# IKO SNA 3-6 plain bearings

Can't find what you're looking for IKO SNA 3-6 plain bearings ? Our expert 420 Outer Diameter (mm) Representatives be in contact 620x420x150 Size (mm) with you shortly!

Size (mm)	620x420x150
Bore Diameter (mm)	620
Outer Diameter (mm)	420
Width (mm)	150
d	420 mm
D	620 mm
B	150 mm
d1	492 mm
D1	556 mm
E	578.2 mm
r1,2 – min.	3 mm
s	13 mm
da – min.	438 mm
Da – max.	602 mm
Db – min.	586 mm
ra – max.	2.5 mm
Basic dynamic load rating – C	2920 kN
Basic static load rating – C0	5400 kN
Fatigue load limit – Pu	430 kN
Reference speed	900 r/min
Limiting speed	1400 r/min
Calculation factor – kr	0.17
d1 ≈	492 mm

D1 ≈	556 mm
r1,2 min.	3 mm
s max.	13 mm
da min.	438 mm
Da max.	602 mm
Db min.	586 mm
ra max.	2.5 mm
Basic dynamic load rating C	2920 kN
Basic static load rating C0	5400 kN
Fatigue load limit Pu	430 kN
Calculation factor kr	0.17
Limiting value e	0.3
Axial load factor Y	0.6
Mass bearing	160 kg