

IKO SNPT 3/8-30 plain bearings

Shop 35 Bore Diameter (mm) IKO SNPT 3/8-30 plain bearings huge online discount inventory. 42 Outer Diameter (mm) and Import 35x42x20 Size (mm) machinery parts your car needs with Free Shipping and Free Extended Warranty.

Size (mm)	35x42x20
Bore Diameter (mm)	35
Outer Diameter (mm)	42
Width (mm)	20
Fw	35 mm
D	42 mm
C	20 mm
r5 min.	1 mm
Weight	0.049 Kg
Basic dynamic load rating (C)	24.5 kN
Basic static load rating (C0)	46.8 kN
(Grease) Lubrication Speed	5900 r/min
Inventory	0.0
Manufacturer Name	KOYO
Minimum Buy Quantity	N/A
Weight / Kilogram	0.054
EAN	0605790199554
Product Group	B04144
Rolling Element	Needle Roller Bearing
Component	Roller Assembly with Outer Ring – No Inner Ring

Enclosure	Open
Self Aligning	No
Retainer	Yes
Number of Rows of Rollers	Single Row
Separable	No
Closed End	No
Inch – Metric	Metric
Relubricatable	No
Thrust Bearing	No
Long Description	35MM Bore; 42MM Outside Diameter; 20MM Width; Needle Roller Bearing; Roller Assembly with Outer Ring
Other Features	2 Rib Outer Ring Drawn Cup Bearing Steel Cage
UNSPSC	31171512
Harmonized Tariff Code	8482.40.00.00
Noun	Bearing
Keyword String	Needle
Manufacturer Item Number	HK3520
Weight / LBS	0.108
Outside Diameter	1.654 Inch 42 Millimeter
Bore	1.378 Inch 35 Millimeter
Width	0.787 Inch 20 Millimeter
Bearing No.	HK3520
C3(min)	0
rs(min)	1
Cr	24.5
C0r	46.8
Cu	7.40

Grease lub.	5900
Oil lub.	9100
(Refer.)Mass(kg)	0.049
Mounting inner ring	JR30x35x20,5