

IKO TA 4030 Z needle roller bearings

170 Million used IKO TA 4030 Z needle roller bearings instantly searchable. Shop our large selection of parts based on brand, price, 75x100x19 Size (mm) description, and location. Order the 100 Outer Diameter (mm) 75 Bore Diameter (mm) with stock ...

Size (mm)	75x100x19
Bore Diameter (mm)	75
Outer Diameter (mm)	100
Width (mm)	19
d	75 mm
D	100 mm
T	19 mm
d1	100 mm
r min.	1 mm
D1	77 mm
da min.	90 mm
Da max.	85 mm
ra max.	1 mm
Weight	0,389 Kg
Basic dynamic load rating (C)	43,5 kN
Basic static load rating (C0)	131 kN
(Grease) Lubrication Speed	2200 r/min
Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A

Weight / Kilogram	0.39
EAN	0029176026461
Product Group	B00308
Rolling Element	Ball Bearing
Thrust Bearing	Yes
Single or Double Direction	Single Direction
Banded	No
Cage Material	Steel
Precision Class	Non-Precision
Component Description	Roller Assembly Plus Raceways
Other Features	Single Row With Flat Seat
Long Description	75MM Bore 1; 77MM Bore 2; 100MM Outside Diameter; 19MM Height; Ball Bearing; Single Direction; Not B
Inch – Metric	Metric
UNSPSC	31171552
Harmonized Tariff Code	8482.10.50.08
Noun	Bearing
Keyword String	Ball Thrust
Manufacturer Item Number	51115
Weight / LBS	0.8576
Overall Height with Aligning Washer	0 Inch 0 Millimeter
Outside Diameter	3.937 Inch 100 Millimeter
Bore 1	2.953 Inch 75 Millimeter
Bore 2	3.031 Inch 77 Millimeter
Height	0.748 Inch 19 Millimeter
bore diameter:	75 mm
static load capacity:	13400 kg

outside diameter:	100 mm
dynamic load capacity:	4450 kg
overall width:	19 mm
operating temperature range:	Maximum of +120 °C
thrust bearing type:	Single-Direction
maximum rpm:	3400 RPM
outside diameter design:	Straight
cage material:	Steel
separable or banded:	Separable
fillet radius:	1 mm
race type:	Flat
series:	511
precision rating:	ABEC 1 (ISO Class Normal)
SRI	4.7
hidYobi	51115
LangID	1
D_	100
SREX	0.04
C	43.5
B_	19
hidTable	ecat_NSSDTB
Oil rpm	3400
SRE	4.7
mass	0.389
GRS rpm	2200
ra	1
SRIX	0.04
D_a	85
SRIN	0

C0	131
SREN	0
D_1	77
Prod_Type3	TB_SD_WFS
da	90
DA_	8.731
Z_	28
yobi	51115
SDM_	87.5
r	1
T_	19
KBRG	5111