## IKO TAM 1420 needle roller bearings

Our 0.0 Inventory highly-skilled and factory-trained service experts have the resources to help you with all your IKO TAM 1420 needle roller bearings needs — including routine maintenance, major repairs, warranty service, and equipment inspections.

Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	11.788
EAN	7316576623554
Product Group	B04144
Bore Profile	Straight
Cage Material	Brass
Precision Class	RBEC 1   ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring — Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C3-Loose
Retainer	Yes
Relubricatable	Yes
Inch — Metric	Metric

Other Features	High Capacity   Plain Inner Ring   2 Rib Outer Ring   Cage on Outer Ring ID
Long Description	110MM Bore; Straight Bore Profile; 240MM Outside Diameter; 50MM Width; Brass Cage Matetrial; RBEC 1
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer Item Number	NU 322 ECM/C3
Weight / LBS	25.964
D	9.449 Inch   240 Millimeter
d	4.331 Inch   110 Millimeter
В	1.969 Inch   50 Millimeter
bore diameter:	110 mm
precision rating:	RBEC 1 (ISO Class Normal)
outside diameter:	240 mm
maximum rpm:	3400 RPM
overall width:	50 mm
bearing material:	Steel
flanges:	(2) Outer Ring
cage material:	Brass
bore type:	Straight
finish/coating:	Uncoated
number of rows:	1
closure type:	0pen
internal clearance:	C3
application:	Piston Type Machines, Rolling Mills, Spindles/Machine Tools

ring separation:	Separable Ring
outer ring width:	50 mm
operating temperature range:	Maximum of +300 °F
fillet radius:	2.5 mm
dynamic load capacity:	530 kN
series:	NU3
static load capacity:	540 kN