

IKO TAM 2215 needle roller bearings

Enjoy High 28 Bore Diameter (mm) Margins on 28x12x8 Size (mm) Competitive Pricing.Great Wholesale Products at Low Costs.

Size (mm)	28x12x8
Bore Diameter (mm)	28
Outer Diameter (mm)	12
Width (mm)	8
d	12 mm
D	28 mm
B	8 mm
d2	16 mm
D2	25.15 mm
r1,2 – min.	0.3 mm
Da – max.	26 mm
ra – max.	0.3 mm
Basic dynamic load rating – C	4.4 kN
Basic static load rating – C0	2.4 kN
Fatigue load limit – Pu	0.102 kN
Reference speed	60000 r/min
Limiting speed	30000 r/min
Calculation factor – kr	0.03
Calculation factor – f0	13.2
d2 ≈	16 mm
D2 ≈	25.15 mm
r1,2 min.	0.3 mm
da min.	14 mm

da max.	15.5 mm
Da max.	26 mm
ra max.	0.3 mm
Basic dynamic load rating C	4.42 kN
Basic static load rating C0	2.36 kN
Fatigue load limit Pu	0.102 kN
Calculation factor kr	0.03
Calculation factor f0	13.2
Mass bearing	0.02 kg