

IKO TAM 2515 needle roller bearings

IKO TAM 2515 needle roller bearings 188.912 mm db Product 163.512 mm dc Brochures , 170 mm da Manufacturing Service .
Get Your Free.

da	170 mm
db	188.912 mm
dc	163.512 mm
Da	309.999 mm
Ca	95.809 mm
A1	171.45 mm
A2	247.65 mm
S	4.763 mm
ba	74.612 mm
H	360.363 mm
H1	179.4 mm
H2	69.85 mm
J min.	492.125 mm
J max.	549.275 mm
J1	107.95 mm
L	628.65 mm
N1	28.575 mm
R1	115.888 mm
R2	37.306 mm
RG	3/4 NPT
PG	1/4 NPT
h	54.769 mm

Housing	SAFS 234
Bearing	22234 CC/W33
Lock nut	AN 34
Lock washer	W 34
Stabilizing ring	SR-34-0
Labyrinth ring (db shaft position)	LOR 161
PosiTrac Plus contact element (db shaft position)	B10724-161
Labyrinth ring (dc shaft position)	LOR 148
PosiTrac Plus contact element (dc shaft position)	B10724-148
End plug (suffix Y)	EPR 19
Max. speed for PosiTrac Plus seal	760 r/min
P60°	345 kN
P90°	207 kN
P120°	127 kN
P150°	113 kN
P180°	113 kN
Pa	73.4 kN
Mass pillow block	157 kg
Cap bolt	1-8 UNC
Cap bolt recommended tightening torque	1220 N·m
Cap bolt, SAE grade	8
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	1 in
Initial grease fill	878.85 g