## IKO YB 45 needle roller bearings

With over 10170 full-service stores, our IKO YB 45 needle roller bearings inventory is extensive and our parts are priced right. within 24 hours. This helps you maximize your productivity by saving Open Type Bearing Style time and your hard-earned 8 Days Days to Ship dollars.

| Days to Ship                 | 8 Days        |
|------------------------------|---------------|
| Inner/Outer Ring Material    | [Steel] Steel |
| Bearing Style                | Open Type     |
| Outer Ring Shape             | Flat          |
| Precision                    | Grade 5       |
| I.D.(Ø)                      | 80            |
| 0.D.(Ø)                      | 170           |
| Width(mm)                    | 39            |
| Basic Dynamic Load Rating(N) | 123000        |
| Rolling Element Material     | [Steel] Steel |
| Retainer Type                | No            |
| Clearance sign               | No            |
| Accuracy(Class)              | Class 0       |
| Acoustic Symbol              | No            |
| Holder Symbol                | No            |
| Symbol of Bearing Ring Shape | No            |
| Seal, Shield Symbols         | No            |
| Precision Grade Symbol       | P5            |
| Special Configurations Code  | No            |
| Rubugado Symbol              | No            |

| Material Symbol             | No              |
|-----------------------------|-----------------|
| Spacer, Sleeve symbol       | No              |
| Types                       | No              |
| Туре                        | Ball            |
| Specifications, Environment | Standard        |
| Load Direction              | Radial          |
| Outer Ring                  | With Outer Ring |
| Number of Raceway Ring Rows | Single Row      |
| Size Standards              | Metric System   |
| Combination symbol          | No              |
| Low Torque Specification    | No              |
| Internal Symbol             | No              |
| Torque Symbol               | No              |
| RoHS                        | 6               |
| d                           | 80              |
| D                           | 170             |
| В                           | 39              |
| Max. Allowed rpm(rpm)       | 4000            |
| Specifications/Environment  | Standard        |
|                             |                 |