

INA BCE1416 needle roller bearings

INA BCE1416 needle roller bearings Warehouse offers 62 mm D car parts and car accessories. We sell discount online as 24 mm d1 well as cheap machinery parts.

| | |
|---------------------------|---------|
| D | 62 mm |
| d1 | 24 mm |
| C | 29 mm |
| F | 30 mm |
| B | 30.5 mm |
| B1 | 80 mm |
| B2 | 49.5 mm |
| G | M24X1.5 |
| G1 | 25 mm |
| B3 | 11 mm |
| C1 | 0.8 mm |
| n | 8 mm |
| a | 4 mm |
| e | 44 mm |
| Dw | 2.5 mm |
| Lw | 20.8 mm |
| Maximum tightening torque | 178 Nm |
| Bearing with/without cage | Avec |
| Radial clearance class | CN |
| Precision class | P0 |
| Mass | 0.79 kg |
| Cr | 28.9 kN |

| | |
|---|-----------|
| C _{0r} | 55 kN |
| Track load capacity cylindrical outer ring | 34.5 kN |
| N _{lim} (grease) | 5,000 rpm |
| N _{lim} (oil) | 6,500 rpm |
| Min operating temperature, T _{min} | -20 °C |
| Max operating temperature, T _{max} | 120 °C |
| Characteristic cage frequency, FTF | 0.46 Hz |
| Characteristic rolling element frequency, BSF | 12.92 Hz |
| Characteristic outer ring frequency, BPF ₀ | 12 Hz |
| Characteristic inner ring frequency, BPF _I | 14 Hz |