

# INA BXRE200-2HRS needle roller bearings

Online 20 mm d shopping 14 mm B INA BXRE200-2HRS needle roller bearings from 47 mm D a great selection at Store. ... Accessories.

d	20 mm
D	47 mm
B	14 mm
E	41.5 mm
F	26.5 mm
d1	29.5 mm
rs min	1 mm
r1s min	0.6 mm
Radial clearance class	CN
Mass (without HJ ring)	0.11 kg
Dynamic load, C	25.7 kN
Static load, C0	22.6 kN
Fatigue limit load, Cu	2.75 kN
Nlim (oil)	18,000 rpm
Nlim (grease)	15,000 rpm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.39 Hz
Characteristic rolling element frequency, BSF	4.31 Hz
Characteristic outer ring frequency, BPF0	4.29 Hz

Characteristic inner ring frequency, BPI	6.71 Hz
da min	25 mm
da max	26 mm
dc min	32 mm
Da max	42 mm
ra max	1 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.109
EAN	4547359117189
Product Group	B04144
bore diameter:	20 mm
static load capacity:	22600 N
outside diameter:	47 mm
precision rating:	ISO Class 0
overall width:	14 mm
maximum rpm:	18000 rpm
flanges:	(2) Outer Ring, (1) Inner Ring
bearing material:	Hardened Alloy Steel
bore type:	Straight
cage material:	Nylon
number of rows:	1
finish/coating:	Uncoated
internal clearance:	CN
closure type:	Open
operating temperature range:	-40 to 120 °C

fillet radius:	1 mm
dynamic load capacity:	25700 N
manufacturer product page:	<a href="#">Click here</a>