INA BXRE209 needle roller bearings

Manufacturers of all are 1.4375 in d represented in our partial list of clients. Contact Gary for a complete INA BXRE209 needle roller bearings list of clients and projects.

d1.4375 inhorizontal bolt spacing:2 inbore type:Roundvertical bolt spacing:1-1/4 induty type:Standard Dutyshaft centerline height:2-3/8 inmounting type:Three-Bolt Bracket Stylehub diameter:3-3/4 inhousing material:PBT Thermoplasticbracket width:3-1/2 inlocking device:Accu-Locunit standoff:2-33/64 inradial dynamic load capacity:5820 lbfbolt size:1/2radial static load capacity:3460 lbflubrication type:Lubrication Fittingseal type:Dual Lip with Slingerseries:UEFBL200MZ20RFCWend type:Openreplacement bearing:UE207-23MZ20RFlength through bore:1.728 in		
bore type:Roundvertical bolt spacing:1-1/4 induty type:Standard Dutyshaft centerline height:2-3/8 inmounting type:Three-Bolt Bracket Stylehub diameter:3-3/4 inhousing material:PBT Thermoplasticbracket width:3-1/2 inlocking device:Accu-Locunit standoff:2-33/64 inradial dynamic load capacity:5820 lbfbolt size:1/2radial static load capacity:3460 lbflubrication type:Lubrication Fittingseal type:Dual Lip with Slingerseries:UEFBL200MZ20RFCWend type:Openreplacement bearing:UE207-23MZ20RF	d	1.4375 in
vertical bolt spacing:1-1/4 induty type:Standard Dutyshaft centerline height:2-3/8 inmounting type:Three-Bolt Bracket Stylehub diameter:3-3/4 inhousing material:PBT Thermoplasticbracket width:3-1/2 inlocking device:Accu-Locunit standoff:2-33/64 inradial dynamic load capacity:5820 lbfbolt size:1/2radial static load capacity:3460 lbflubrication type:Lubrication Fittingseal type:Dual Lip with Slingerseries:UEFBL200MZ20RFCWend type:Openreplacement bearing:UE207-23MZ20RF	horizontal bolt spacing:	2 in
duty type:Standard Dutyshaft centerline height:2-3/8 inmounting type:Three-Bolt Bracket Stylehub diameter:3-3/4 inhousing material:PBT Thermoplasticbracket width:3-1/2 inlocking device:Accu-Locunit standoff:2-33/64 inradial dynamic load capacity:5820 lbfbolt size:1/2radial static load capacity:3460 lbflubrication type:Lubrication Fittingseal type:Dual Lip with Slingerseries:UEFBL200MZ20RFCWend type:Openreplacement bearing:UE207-23MZ20RF	bore type:	Round
shaft centerline height:2-3/8 inmounting type:Three-Bolt Bracket Stylehub diameter:3-3/4 inhousing material:PBT Thermoplasticbracket width:3-1/2 inlocking device:Accu-Locunit standoff:2-33/64 inradial dynamic load capacity:5820 lbfbolt size:1/2radial static load capacity:3460 lbflubrication type:Lubrication Fittingseal type:Dual Lip with Slingerend type:Openreplacement bearing:UE207-23MZ20RF	vertical bolt spacing:	1-1/4 in
mounting type:Three-Bolt Bracket Stylehub diameter:3-3/4 inhousing material:PBT Thermoplasticbracket width:3-1/2 inlocking device:Accu-Locunit standoff:2-33/64 inradial dynamic load capacity:5820 lbfbolt size:1/2radial static load capacity:3460 lbflubrication type:Lubrication Fittingseal type:Dual Lip with Slingerseries:UEFBL200MZ20RFCWend type:Openreplacement bearing:UE207-23MZ20RF	duty type:	Standard Duty
hub diameter:3-3/4 inhousing material:PBT Thermoplasticbracket width:3-1/2 inlocking device:Accu-Locunit standoff:2-33/64 inradial dynamic load capacity:5820 lbfbolt size:1/2radial static load capacity:3460 lbflubrication type:Lubrication Fittingseal type:Dual Lip with Slingerseries:UEFBL200MZ20RFCWend type:Openreplacement bearing:UE207-23MZ20RF	shaft centerline height:	2-3/8 in
housing material:PBT Thermoplasticbracket width:3-1/2 inlocking device:Accu-Locunit standoff:2-33/64 inradial dynamic load capacity:5820 lbfbolt size:1/2radial static load capacity:3460 lbflubrication type:Lubrication Fittingseal type:Dual Lip with Slingerseries:UEFBL200MZ20RFCWend type:Openreplacement bearing:UE207-23MZ20RF	mounting type:	Three-Bolt Bracket Style
bracket width:3-1/2 inlocking device:Accu-Locunit standoff:2-33/64 inradial dynamic load capacity:5820 lbfbolt size:1/2radial static load capacity:3460 lbflubrication type:Lubrication Fittingseal type:Dual Lip with Slingerseries:UEFBL200MZ20RFCWend type:Openreplacement bearing:UE207-23MZ20RF	hub diameter:	3-3/4 in
locking device:Accu-Locunit standoff:2-33/64 inradial dynamic load capacity:5820 lbfbolt size:1/2radial static load capacity:3460 lbflubrication type:Lubrication Fittingseal type:Dual Lip with Slingerseries:UEFBL200MZ20RFCWend type:Openreplacement bearing:UE207-23MZ20RF	housing material:	PBT Thermoplastic
unit standoff:2-33/64 inradial dynamic load capacity:5820 lbfbolt size:1/2radial static load capacity:3460 lbflubrication type:Lubrication Fittingseal type:Dual Lip with Slingerseries:UEFBL200MZ20RFCWend type:Openreplacement bearing:UE207-23MZ20RF	bracket width:	3-1/2 in
radial dynamic load capacity: 5820 lbf bolt size: 1/2 radial static load capacity: 3460 lbf lubrication type: Lubrication Fitting seal type: Dual Lip with Slinger series: UEFBL200MZ20RFCW end type: 0pen replacement bearing: UE207-23MZ20RF	locking device:	Accu-Loc
bolt size:1/2radial static load capacity:3460 lbflubrication type:Lubrication Fittingseal type:Dual Lip with Slingerseries:UEFBL200MZ20RFCWend type:Openreplacement bearing:UE207-23MZ20RF	unit standoff:	2-33/64 in
radial static load capacity: 3460 lbf lubrication type: Lubrication Fitting seal type: Dual Lip with Slinger series: UEFBL200MZ20RFCW end type: Open replacement bearing: UE207-23MZ20RF	radial dynamic load capacity:	5820 lbf
lubrication type:Lubrication Fittingseal type:Dual Lip with Slingerseries:UEFBL200MZ20RFCWend type:Openreplacement bearing:UE207-23MZ20RF	bolt size:	1/2
seal type: Dual Lip with Slinger series: UEFBL200MZ20RFCW end type: Open replacement bearing: UE207-23MZ20RF	radial static load capacity:	3460 lbf
series: UEFBL200MZ20RFCW end type: Open replacement bearing: UE207-23MZ20RF	lubrication type:	Lubrication Fitting
end type: Open replacement bearing: UE207-23MZ20RF	seal type:	Dual Lip with Slinger
replacement bearing: UE207-23MZ20RF	series:	UEFBL200MZ20RFCW
	end type:	0pen
length through bore: 1.728 in	replacement bearing:	UE207-23MZ20RF
	length through bore:	1.728 in