

INA CSXC100 deep groove ball bearings

INA CSXC100 deep groove ball bearings Warehouse offers car parts and car 127×228.6×53.975 Size (mm) accessories. We sell discount 127 Bore Diameter (mm) online as well as cheap machinery parts.

Size (mm)	127×228.6×53.975
Bore Diameter (mm)	127
Outer Diameter (mm)	228,6
Width (mm)	53,975
d	127 mm
D	228,6 mm
T	53,975 mm
B	49,428 mm
C	38,1 mm
ra1 max.	3,3 mm
a –	13,5 mm
Da	200 mm
db	143 mm
ra max.	3,5 mm
da	156 mm
Db	219 mm
Weight	8,83 Kg
Basic dynamic load rating (C)	430 kN
Basic static load rating (C0)	620 kN
(Grease) Lubrication Speed	1 400 r/min
(Oil) Lubrication Speed	1 900 r/min

Calculation factor (e)	0,74
Calculation factor (Y0)	0,45
d1	180 mm
a	67.48 mm
e	0.74
Y2	0.81
Y0	0.45
Mass	8.83 kg
Dynamic load, C	430 kN
Rating life coefficient, A2	1.4
Static load, C0	620 kN
Fatigue limit load, Cu	63.7 kN
Nlim (oil)	1,900 rpm
Nlim (grease)	1,400 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.44 Hz
Characteristic rolling element frequency, BSF	7.01 Hz
Characteristic outer ring frequency, BPF0	8.74 Hz
Characteristic inner ring frequency, BRFI	11.26 Hz
ra max	3.5 mm
rla max	3.3 mm