

INA F-236947.2 cylindrical roller bearings

Can't find what you're looking for INA F-236947.2 cylindrical roller bearings ? Our expert Representatives 80x125x22 Size (mm) be in contact with you 80 Bore Diameter (mm) shortly!

Size (mm)	80x125x22
Bore Diameter (mm)	80
Outer Diameter (mm)	125
Width (mm)	22
d	80 mm
D	125 mm
B	22 mm
C	22 mm
r min.	1,1 mm
da min.	86,5 mm
da max	91,5 mm
Da max.	118,5 mm
ra max.	1 mm
Weight	0,854 Kg
Basic dynamic load rating (C)	47,5 kN
Basic static load rating (C0)	40 kN
(Grease) Lubrication Speed	5 300 r/min
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	4547359004182

Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Non-Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	80MM Bore; 125MM Outside Diameter; 22MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No
Other Features	Deep Groove Non-Friction Nitrile Rubber Seal Shell Alvania Prelubricated
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	1.91802
Outside Diameter	4.921 Inch 125 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Bore	3.15 Inch 80 Millimeter
Outer Race Width	0.866 Inch 22 Millimeter
bore diameter:	80 mm
static load capacity:	40000 N
outside diameter:	125 mm

precision rating:	ISO Class 0
overall width:	22 mm
finish/coating:	Uncoated
bore type:	Round
bearing material:	High Carbon Chrome Steel
closure type:	Double Sealed
cage material:	Steel
row type & fill slot:	Single Row Non-Fill Slot
inner ring width:	22 mm
snap ring included:	Without Snap Ring
outer ring width:	22 mm
internal clearance:	CN
maximum rpm (grease):	5300 rpm
operating temperature range:	-40 to 120 °C
fillet radius:	1.1 mm
dynamic load capacity:	47500 N
manufacturer product page:	Click here