INA GAKR 14 PW plain bearings

Manufacturers of all are 32 mm A represented in our partial 12 mm A1 list of clients. Contact Gary for a complete INA GAKR 14 PW plain bearings list of clients and projects.

A1 12 mm A2 21 mm B 31 mm A5 18.3 mm d 15 mm G M6x1 H 89 mm H1 76 mm L 94 mm L 94 mm L1 61 mm L2 10 mm L3 51 mm N 19mm N 19mm N1 16 mm N2 32 mm P 150 mm S 12.7 mm S W 3 mm Z 15.7 mm C 12.8 kN		
A2	A	32 mm
B 31 mm A5 18.3 mm d 15 mm G M6x1 H 89 mm H1 76 mm H2 51 mm L 94 mm L1 61 mm L2 10 mm L3 51 mm N 19mm N1 16 mm N2 32 mm P 150 mm s1 5.5 mm S 3 mm Z 15.7 mm	A1	12 mm
A5 18.3 mm d 15 mm G M6x1 H 89 mm H1 76 mm H2 51 mm L 94 mm L1 61 mm L2 10 mm L3 51 mm N 19mm N 19mm N1 16 mm N2 32 mm P 150 mm \$1 15.5 mm S 12.7 mm SW 3 mm Z 15.7 mm	A2	21 mm
d 15 mm G M6x1 H 89 mm H1 76 mm H2 51 mm L 94 mm L1 61 mm L2 10 mm L3 51 mm N 19mm N1 16 mm N2 32 mm P 150 mm s1 15.5 mm S 12.7 mm SW 3 mm Z 15.7 mm	В	31 mm
G M6x1 H 89 mm H1 76 mm H2 51 mm L 94 mm L1 61 mm L2 10 mm L3 51 mm N 19mm N1 16 mm N2 32 mm P 150 mm s1 15.5 mm S 12.7 mm SW 3 mm Z 15.7 mm	A5	18.3 mm
H H1 H2 F1 Mm H2 F1 Mm H2 H3 H4 H4 H5 H6 H7	d	15 mm
H1 76 mm H2 51 mm L 94 mm L1 61 mm L2 10 mm L3 51 mm N 19mm N1 16 mm N2 32 mm P 150 mm s1 15.5 mm S W 3 mm Z 15.7 mm	G	M6x1
H2 51 mm L 94 mm L1 61 mm L2 10 mm L3 51 mm N 19mm N1 16 mm N2 32 mm P 150 mm \$1 15.5 mm \$ 12.7 mm \$ W Z 15.7 mm	Н	89 mm
L 94 mm L1 61 mm L2 10 mm L3 51 mm N 19mm N1 16 mm N2 32 mm P 150 mm s1 15.5 mm S 12.7 mm SW 3 mm Z 15.7 mm	H1	76 mm
L1 61 mm L2 10 mm L3 51 mm N 19mm N1 16 mm N2 32 mm P 150 mm s1 15.5 mm S 12.7 mm SW 3 mm Z 15.7 mm	H2	51 mm
L2 10 mm L3 51 mm N 19mm N1 16 mm N2 32 mm P 150 mm s1 15.5 mm S 12.7 mm SW 3 mm Z 15.7 mm	L	94 mm
L3 51 mm N 19mm N1 16 mm N2 32 mm P 150 mm s1 15.5 mm S 12.7 mm SW 3 mm Z 15.7 mm	L1	61 mm
N 19mm N1 16 mm N2 32 mm P 150 mm s1 15.5 mm S 12.7 mm SW 3 mm Z 15.7 mm	L2	10 mm
N1 16 mm N2 32 mm P 150 mm s1 15.5 mm S 12.7 mm SW 3 mm Z 15.7 mm	L3	51 mm
N2 32 mm P 150 mm s1 15.5 mm S 12.7 mm SW 3 mm Z 15.7 mm	N	19mm
P 150 mm s1 15.5 mm S 12.7 mm SW 3 mm Z 15.7 mm	N1	16 mm
s1 15.5 mm S 12.7 mm SW 3 mm Z 15.7 mm	N2	32 mm
S 12.7 mm SW 3 mm Z 15.7 mm	Р	150 mm
SW 3 mm Z 15.7 mm	s1	15.5 mm
Z 15.7 mm	S	12.7 mm
	SW	3 mm
C 12.8 kN	Z	15.7 mm
	С	12.8 kN

C0	6.65 kN
T min.	-20 °C
T max.	100 °C
Weight	0.8 kg
Recommended tightening torque for set screw	5.5 Nm
Designation of housing	T204N-
Designation of bearing	UC202G2L4