

INA GAY008-NPP-B-AS2/V deep groove ball bearings

INA GAY008-NPP-B-AS2/V deep groove ball bearings 112.713 mm da
 Manufacturers , 200 mm Da Online Wholesale Suppliers ! 62.789
 mm Ca

| | |
|-------------------------|-----------------|
| da | 112.713 mm |
| Da | 200 mm |
| Ca | 62.789 mm |
| A1 | 120.65 mm |
| A2 | 165.1 mm |
| ba | 51.594 mm |
| H | 244.475 mm |
| H1 | 125.425 mm |
| H2 | 52.388 mm |
| J min. | 320.675 mm |
| J max. | 368.3 mm |
| J1 | 69.85 mm |
| L | 419.1 mm |
| N1 | 24.209 mm |
| R1 | 73.025 mm |
| R2 | 31.75 mm |
| RG | 3/8 NPT |
| PG | 1/4 NPT |
| h | 40.922 mm |
| Housing | SAFS 026 KA |
| Bearing | 23026 CCK/W33 |
| Adapter sleeve assembly | SNW 3026×4.7/16 |

| | |
|--|----------------|
| Stabilizing ring | 2 x 38151-26 |
| Labyrinth ring | 2 x LOR 117 |
| PosiTrac Plus contact element | 2 x B10724-117 |
| End plug (suffix Y) | EPR 15 |
| Max. speed for PosiTrac Plus seal | 1300 r/min |
| P60° | 178 kN |
| P90° | 107 kN |
| P120° | 66.7 kN |
| P150° | 59.6 kN |
| P180° | 72.5 kN |
| Pa | 20.2 kN |
| Mass pillow block | 50.8 kg |
| Cap bolt | 5/8-11 UNC |
| Cap bolt recommended tightening torque | 298.3 N·m |
| Cap bolt, SAE grade | 8 |
| Eye bolt | 2 x 3/8-16 UNC |
| Appropriate attachment bolt size G | 0.75 in |
| Initial grease fill | 232.47 g |