

# INA GAY008-NPP-B-AS2/V deep groove ball bearings

INA GAY008-NPP-B-AS2/V deep groove ball bearings 112.713 mm da  
 Manufacturers , 200 mm Da Online Wholesale Suppliers ! 62.789 mm Ca

|                         |                 |
|-------------------------|-----------------|
| da                      | 112.713 mm      |
| Da                      | 200 mm          |
| Ca                      | 62.789 mm       |
| A1                      | 120.65 mm       |
| A2                      | 165.1 mm        |
| ba                      | 51.594 mm       |
| H                       | 244.475 mm      |
| H1                      | 125.425 mm      |
| H2                      | 52.388 mm       |
| J min.                  | 320.675 mm      |
| J max.                  | 368.3 mm        |
| J1                      | 69.85 mm        |
| L                       | 419.1 mm        |
| N1                      | 24.209 mm       |
| R1                      | 73.025 mm       |
| R2                      | 31.75 mm        |
| RG                      | 3/8 NPT         |
| PG                      | 1/4 NPT         |
| h                       | 40.922 mm       |
| Housing                 | SAFS 026 KA     |
| Bearing                 | 23026 CCK/W33   |
| Adapter sleeve assembly | SNW 3026×4.7/16 |

|  |                |
|--|----------------|
| Stabilizing ring                       | 2 x 38151-26   |
| Labyrinth ring                         | 2 x LOR 117    |
| PosiTrac Plus contact element          | 2 x B10724-117 |
| End plug (suffix Y)                    | EPR 15         |
| Max. speed for PosiTrac Plus seal      | 1300 r/min     |
| P60°                                   | 178 kN         |
| P90°                                   | 107 kN         |
| P120°                                  | 66.7 kN        |
| P150°                                  | 59.6 kN        |
| P180°                                  | 72.5 kN        |
| Pa                                     | 20.2 kN        |
| Mass pillow block                      | 50.8 kg        |
| Cap bolt                               | 5/8-11 UNC     |
| Cap bolt recommended tightening torque | 298.3 N·m      |
| Cap bolt, SAE grade                    | 8              |
| Eye bolt                               | 2 x 3/8-16 UNC |
| Appropriate attachment bolt size G     | 0.75 in        |
| Initial grease fill                    | 232.47 g       |