INA GE 100 SX plain bearings

Our highly-skilled and factory-trained service experts have the resources to help you with all Angular Contact Ball Bearing (Single Row) Type your INA GE 100 SX plain bearings Quote Days to Ship needs — including routine maintenance, major repairs, warranty service, and equipment inspections.

Days to Ship	Quote
Туре	Angular Contact Ball Bearing (Single Row)
Inner/Outer Ring Material	[Steel] Steel
Bearing Style	Open Type
Precision	Grade 4
I.D.(Ø)	75
0.D.(Ø)	115
Width(mm)	20
Basic Dynamic Load Rating(N)	48000
Max. Allowed rpm(rpm)	8500
Specifications, Environment	Standard
Rolling Element Material	[Steel] Steel
Combination of Angular Contact Ball Bearings	Single Row
Retainer Type	Resin Forming
Basic Load Rating, Static Rating(N)	45500
Clearance sign	No
Preload	Light Preload
Contact angle(Degree)	40
Holder Symbol	TYN

Symbol of Bearing Ring Shape	No
Seal, Shield Symbols	No
Precision Grade Symbol	P4
Symbol of contact angle	С
Combination symbol	SU
Preload Mark	L
Special Configurations Code	No
Bearing type symbol	No
Type symbol	No
Outer Ring Shape	Flat
Load Direction	Radial
Outer Ring	With Outer Ring
Size Standards	Metric System