

INA GE 120 D0 plain bearings

What are the types of INA GE 120 D0 plain bearings ?
Manufacturing Service . Get Your Free, 168.275 mm db Instant price, design review. 150 mm da

| | |
|---------|------------|
| da | 150 mm |
| db | 168.275 mm |
| dc | 146.05 mm |
| Da | 269.999 mm |
| Ca | 105.816 mm |
| A1 | 158.75 mm |
| A2 | 238.125 mm |
| S | 4.763 mm |
| ba | 77.787 mm |
| H | 317.5 mm |
| H1 | 160.35 mm |
| H2 | 63.5 mm |
| J min. | 431.8 mm |
| J max. | 463.55 mm |
| J1 | 95.25 mm |
| L | 539.75 mm |
| N1 | 28.575 mm |
| R1 | 95.25 mm |
| R2 | 39.688 mm |
| RG | 3/4 NPT |
| PG | 1/4 NPT |
| h | 50.8 mm |
| Housing | SAW 230 |

| | |
|---|----------------|
| Bearing | 23230 CC/W33 |
| Lock nut | AN 30 |
| Lock washer | W 30 |
| Stabilizing ring | SR-30-0 |
| Labyrinth ring (db shaft position) | LOR 151 |
| PosiTrac Plus contact element (db shaft position) | B10724-151 |
| Labyrinth ring (dc shaft position) | LOR 134 |
| PosiTrac Plus contact element (dc shaft position) | B10724-134 |
| End plug (suffix Y) | EPR 17 |
| Max. speed for PosiTrac Plus seal | 850 r/min |
| P60° | 230 kN |
| P90° | 138 kN |
| P120° | 87.2 kN |
| P150° | 80.1 kN |
| P180° | 96.1 kN |
| Pa | 43.2 kN |
| Mass pillow block | 92.5 kg |
| Cap bolt | 4 x 3/4-10 UNC |
| Cap bolt recommended tightening torque | 359.3 N·m |
| Cap bolt, SAE grade | 5 |
| Eye bolt | 2 x 3/8-16 UNC |
| Appropriate attachment bolt size G | 1 in |
| Initial grease fill | 623.7 g |