

INA GE 20 FW plain bearings

INA GE 20 FW plain bearings Industries and 190 Outer Diameter (mm) Applications ? We sell discount online as well 340x190x55 Size (mm) as cheap machinery parts.

| | |
|-------------------------------|------------|
| Size (mm) | 340x190x55 |
| Bore Diameter (mm) | 340 |
| Outer Diameter (mm) | 190 |
| Width (mm) | 55 |
| d | 190 mm |
| D | 340 mm |
| B | 55 mm |
| d1 | 244 mm |
| D1 | 295 mm |
| F | 230 mm |
| r1,2 – min. | 4 mm |
| r3,4 – min. | 4 mm |
| da – min. | 207 mm |
| db – min. | 248 mm |
| Da – max. | 321.9 mm |
| ra – max. | 3 mm |
| Basic dynamic load rating – C | 800 kN |
| Basic static load rating – C0 | 965 kN |
| Fatigue load limit – Pu | 98 kN |
| Reference speed | 2000 r/min |
| Limiting speed | 3400 r/min |
| Calculation factor – kr | 0.23 |
| bore diameter: | 190 mm |

| | |
|------------------------------|---|
| static load capacity: | 965 kN |
| outside diameter: | 340 mm |
| maximum rpm: | 3400 rpm |
| overall width: | 55 mm |
| bearing material: | Steel |
| flanges: | (2) Flanges on outer Ring, Flangeless Inner Ring |
| cage material: | Brass |
| bore type: | Straight |
| finish/coating: | Uncoated |
| number of rows: | 1 |
| closure type: | Open |
| operating temperature range: | Maximum 302 °F |
| series: | NUP |
| dynamic load capacity: | 800 kN |
| manufacturer upc number: | 7316575448806 |
| d1 ≈ | 244 mm |
| D1 ≈ | 295 mm |
| r1,2 min. | 4 mm |
| r3,4 min. | 4 mm |
| da min. | 207 mm |
| db min. | 248 mm |
| Da max. | 321.9 mm |
| ra max. | 3 mm |
| Basic dynamic load rating C | 800 kN |
| Basic static load rating C0 | 965 kN |
| Fatigue load limit Pu | 98 kN |
| Calculation factor kr | 0.23 |
| Limiting value e | 0.2 |

| | |
|---------------------|---------|
| Axial load factor Y | 0.6 |
| Mass bearing | 22.6 kg |