## INA GE 30 UK-2RS plain bearings

INA GE 30 UK-2RS plain bearings Warehouse offers car parts and car accessories. We sell discount online as well 0.0 Inventory as cheap machinery TIMKEN Manufacturer Name parts.

Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	9.988
EAN	0883450063135
Product Group	M06288
Number of Mounting Holes	4
Mounting Method	Eccentric Collar
Housing Style	4 Bolt Round Flange Cartridge
Rolling Element	Spherical Roller Bearing
Housing Material	Cast Steel
Expansion / Non-expansion	Non-expansion
Mounting Bolts	5/8 Inch
Relubricatable	Yes
Insert Part Number	22215
Seals	Double Lip Viton
Housing Configuration	1 Piece Solid
Pilot Configuration	With Pilot
Inch — Metric	Inch
Long Description	<pre>4 Bolt Round Flange Cartridge; 3" Bore; 7-1/2" Bolt Circle; 5.3" Bolt Spacing; 1 Piec</pre>

Other FeaturesDouble RowUNSPSC31171501Harmonized Tariff Code8483.20.40.80NounBearingKeyword StringFlangedWeight / LBS22Bolt Spacing5.3 Inch   134.7 MillimeterNominal Bolt Circle Diameter Round7.5 Inch   190 MillimeterD3 Inch   76.2 MillimeterD3.62 Inch   91.948 MillimeterCartridge Pilot Depth0 Inch   0 Millimeter		
Harmonized Tariff Code8483.20.40.80NounBearingKeyword StringFlangedWeight / LBS22Bolt Spacing5.3 Inch   134.7 MillimeterNominal Bolt Circle Diameter Round7.5 Inch   190 Millimeterd3 Inch   76.2 MillimeterD3.62 Inch   91.948 Millimeter	Other Features	Double Row
NounBearingKeyword StringFlangedWeight / LBS22Bolt Spacing5.3 Inch   134.7 MillimeterNominal Bolt Circle Diameter Round7.5 Inch   190 Millimeterd3 Inch   76.2 MillimeterD3.62 Inch   91.948 MillimeterCartridge Pilot Depth0 Inch   0 Millimeter	UNSPSC	31171501
Keyword StringFlangedWeight / LBS22Bolt Spacing5.3 Inch   134.7 MillimeterNominal Bolt Circle Diameter Round7.5 Inch   190 Millimeterd3 Inch   76.2 MillimeterD3.62 Inch   91.948 MillimeterCartridge Pilot Depth0 Inch   0 Millimeter	Harmonized Tariff Code	8483.20.40.80
Weight / LBS22Bolt Spacing5.3 Inch   134.7 MillimeterNominal Bolt Circle Diameter Round7.5 Inch   190 Millimeterd3 Inch   76.2 MillimeterD3.62 Inch   91.948 MillimeterCartridge Pilot Depth0 Inch   0 Millimeter	Noun	Bearing
Bolt Spacing5.3 Inch   134.7 MillimeterNominal Bolt Circle Diameter Round7.5 Inch   190 Millimeterd3 Inch   76.2 MillimeterD3.62 Inch   91.948 MillimeterCartridge Pilot Depth0 Inch   0 Millimeter	Keyword String	Flanged
Nominal Bolt Circle Diameter Round7.5 Inch   190 Millimeterd3 Inch   76.2 MillimeterD3.62 Inch   91.948 MillimeterCartridge Pilot Depth0 Inch   0 Millimeter	Weight / LBS	22
Round7.5 Inch   190 Millimeterd3 Inch   76.2 MillimeterD3.62 Inch   91.948 MillimeterCartridge Pilot Depth0 Inch   0 Millimeter	Bolt Spacing	5.3 Inch   134.7 Millimeter
D3.62 Inch   91.948 MillimeterCartridge Pilot Depth0 Inch   0 Millimeter		7.5 Inch   190 Millimeter
Cartridge Pilot Depth 0 Inch   0 Millimeter	d	3 Inch   76.2 Millimeter
	D	3.62 Inch   91.948 Millimeter
Cartridge Pilot Diameter 6.375 Inch   161.92 Millimeter	Cartridge Pilot Depth	0 Inch   0 Millimeter
	Cartridge Pilot Diameter	6.375 Inch   161.92 Millimeter