

INA GE30-KLL-B deep groove ball bearings

INA GE30-KLL-B deep groove ball bearings Industries 20 Bore Diameter (mm) and Applications ? We sell discount online 20x40x26 Size (mm) as well as cheap machinery parts.

Size (mm)	20x40x26
Bore Diameter (mm)	20
Outer Diameter (mm)	40
Width (mm)	26
d	20 mm
d2	15 mm
D	40 mm
T	26 mm
ra1 max.	0.3 mm
T1	16 mm
a	6 mm
d3	40 mm
r min.	0.6 mm
r1 min.	0.3 mm
D1	22 mm
D2	30 mm
D3	42 mm
da min.	20 mm
Da max.	28 mm
ra max.	0.6 mm
Weight	0.150 Kg
Basic dynamic load rating (C)	22,2 kN

Basic static load rating (C0)	37,5 kN
(Grease) Lubrication Speed	4200 r/min
Inventory	0.0
Manufacturer Name	NACHI
Minimum Buy Quantity	N/A
Weight / Kilogram	0
Product Group	B00234
Rolling Element	Ball Bearing
Thrust Bearing	Yes
Single or Double Direction	Double Direction
Banded	No
Cage Material	Steel
Precision Class	Non-Precision
Component Description	Roller Assembly Plus Raceways
Other Features	Double Row With Flat Seat
Long Description	15MM Bore 1; 22MM Bore 2; 40MM Outside Diameter; 26MM Height; Ball Bearing; Double Direction; Not Ba
Inch – Metric	Metric
UNSPSC	31171552
Harmonized Tariff Code	8482.10.50.08
Noun	Bearing
Keyword String	Ball Thrust
Weight / LBS	0.33069
Outside Diameter	1.575 Inch 40 Millimeter
Bore 1	0.591 Inch 15 Millimeter
Bore 2	0.866 Inch 22 Millimeter
Overall Height with Aligning Washer	0 Inch 0 Millimeter

Height

1.024 Inch | 26 Millimeter