

INA GIHN-K 63 L0 plain bearings

INA GIHN-K 63 L0 plain bearings 85.725×168.275×41.275 Size (mm) Engineering Calculator , 85,725 Bore Diameter (mm) Manufacturing Service . Get Your Free.

| | |
|-------------------------------|-----------------------|
| Size (mm) | 85.725×168.275×41.275 |
| Bore Diameter (mm) | 85,725 |
| Outer Diameter (mm) | 168,275 |
| Width (mm) | 41,275 |
| d | 85,725 mm |
| D | 168,275 mm |
| T | 41,275 mm |
| B | 41,275 mm |
| C | 30,162 mm |
| ra1 max. | 3,3 mm |
| a | 38,3 mm |
| r min. | 3,5 mm |
| r1 min. | 3,3 mm |
| Da | 149 mm |
| db | 99 mm |
| ra max. | 3,5 mm |
| da | 105 mm |
| Db | 160 mm |
| Weight | 4,15 Kg |
| Basic dynamic load rating (C) | 223 kN |
| Basic static load rating (C0) | 345 kN |
| (Grease) Lubrication Speed | 2000 r/min |

| | |
|-------------------------|-------------|
| (Oil) Lubrication Speed | 2800 r/min |
| Calculation factor (e) | 0,47 |
| Calculation factor (Y0) | 0,7 |
| LangID | 1 |
| ALP23 | 0 |
| outer r | 3.3 |
| ALP22 | 50 |
| D_ | 168.275 |
| ALP21 | 34 |
| SHOG_yobi | 677R/672R |
| RAr | 259.404 |
| inner r | 3.5 |
| GRS rpm | 2000 |
| D_b | 160 |
| D_a | 149 |
| DE_ | 146.822 |
| SLR | 28 |
| Prod_Type3 | TRBSR_ID_A |
| BETA_ | 1 |
| ALPHA_ | 17.417 |
| SDM_ | 132.538 |
| DA1 | 15.843 |
| DA2 | 14.14 |
| hidYobi | 677/672 |
| Y1 | 1.3 |
| B_ | 41.275 |
| Oil rpm | 2800 |
| hidTable | ecat_NSTPRI |
| Y0 | 0.7 |

| | |
|----------|---------|
| inner ra | 3.5 |
| outer rb | 3.3 |
| C0 | 345 |
| CUP | 1.24 |
| e | 0.47 |
| DA_ | 14.996 |
| BET21 | 3 |
| BET22 | 30 |
| BET23 | 0 |
| Z_ | 23 |
| C_ | 30.162 |
| yobi | 677/672 |
| KBRG | 3161 |
| CONE | 2.91 |
| DI_ | 118.001 |