

INA HK0606 needle roller bearings

INA HK0606 needle roller bearings Manufacturers , 150.813 mm da 309.999 mm Da Online Wholesale Suppliers ! 95.809 mm Ca

da	150.813 mm
Da	309.999 mm
Ca	95.809 mm
A1	171.45 mm
A2	309.563 mm
S	4.763 mm
ba	74.612 mm
H	360.363 mm
H1	179.4 mm
H2	69.85 mm
J min.	492.125 mm
J max.	549.275 mm
J1	107.95 mm
L	628.65 mm
N1	28.575 mm
R1	115.888 mm
R2	37.306 mm
RG	3/4 NPT
PG	1/4 NPT
h	54.769 mm
Housing	SAFS 534
Bearing	22234 CCK/W33
Adapter sleeve assembly	SNW 34×5.15/16

Stabilizing ring	SR-34-0
Taconite seal	TER 140
End plug (suffix Y)	EPR 18
Max. speed for Taconite seal	520 r/min
P60°	345 kN
P90°	207 kN
P120°	127 kN
P150°	113 kN
P180°	133 kN
Pa	43.6 kN
Mass pillow block	165 kg
Cap bolt	1-8 UNC
Cap bolt recommended tightening torque	1220 N·m
Cap bolt, SAE grade	8
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	1 in
Initial grease fill	878.85 g