

INA K28X40X25 needle roller bearings

Question INA K28X40X25 needle roller bearings ? Find what 0.0 Inventory you need faster NSK Manufacturer Name by entering your information .

| | |
|---------------------------------|--|
| Inventory | 0.0 |
| Manufacturer Name | NSK |
| Minimum Buy Quantity | N/A |
| Weight | 0.41 |
| EAN | 0029176101717 |
| Product Group | B00308 |
| Enclosure | Open |
| Flush Ground | Yes |
| Rolling Element | Ball Bearing |
| Number of Rows of Balls | Single Row |
| Precision Class | ABEC 3 ISO P6 |
| Maximum Capacity / Filling Slot | No |
| Snap Ring | No |
| Cage Material | Brass |
| Contact Angle | 40 Degree |
| Internal Clearance | C0-Medium |
| Number of Bearings | 1 (Single) |
| Mounting Arrangement | Universal |
| Inch – Metric | Metric |
| Long Description | 40MM Bore; 80MM Outside Diameter; 18MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Ba |

| | |
|-------------------------------|----------------------------|
| UNSPSC | 31171531 |
| Harmonized Tariff Code | 8482.10.50.28 |
| Noun | Bearing |
| Keyword String | Angular Contact |
| Manufacturer Item Number | 7208BMPC |
| Weight / LBS | 0.41 |
| d | 1.575 Inch 40 Millimeter |
| B | 0.709 Inch 18 Millimeter |
| D | 3.15 Inch 80 Millimeter |
| bore diameter: | 40 mm |
| operating temperature range: | Maximum of +250 °F |
| outside diameter: | 80 mm |
| cage material: | Brass |
| overall width: | 18 mm |
| outer ring width: | 18 mm |
| contact angle: | 40 ° |
| maximum rpm: | 9000 RPM |
| row type & fill slot: | Single-Row Non-Fill Slot |
| finish/coating: | Uncoated |
| internal clearance: | C0 |
| precision rating: | ABEC 3 (ISO Class 6) |
| closure type: | Open |
| fillet radius: | 1.1 mm |
| radial dynamic load capacity: | 3250 kgf |
| series: | 72 |
| radial static load capacity: | 2340 kgf |