

INA NA49/32-XL needle roller bearings

offers a INA NA49/32-XL needle roller bearings selection 100 mm d of 215 mm D Genuine at Wholesale Prices. We are a INA NA49/32-XL needle roller bearings Certified Parts Retailer

d	100 mm
D	215 mm
B	47 mm
E	185.5 mm
F	129.5 mm
rs min	3 mm
r1s min	3 mm
Radial clearance class	C3
Mass (without HJ ring)	8.32 kg
Dynamic load, C	299 kN
Static load, C0	335 kN
Fatigue limit load, Cu	35.6 kN
Nlim (oil)	3,800 rpm
Nlim (grease)	3,300 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.41 Hz
Characteristic rolling element frequency, BSF	5.45 Hz
Characteristic outer ring frequency, BPF0	5.34 Hz

Characteristic inner ring frequency, BPI	7.66 Hz
da min	113 mm
da max	125 mm
db min	132 mm
Da max	202 mm
ra max	2.5 mm
r1a max	2.5 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	8.15
EAN	4547359147636
Product Group	B04144
Bore Profile	Straight
Cage Material	Brass
Precision Class	RBEC 1 ISO P0
Number of Rows of Rollers	Single Row
Separable	Inner Ring – Both Sides
Rolling Element	Cylindrical Roller Bearing
Profile	Complete with Outer and Inner Ring
Snap Ring	No
Internal Clearance	C3-Loose
Retainer	Yes
Relubricatable	Yes
Inch – Metric	Metric
Other Features	Plain Inner Ring 2 Rib Outer Ring Cage on Outer Ring ID

Long Description	100MM Bore; Straight Bore Profile; 215MM Outside Diameter; 47MM Width; Brass Cage Material; RBEC 1
UNSPSC	31171547
Harmonized Tariff Code	8482.50.00.00
Noun	Bearing
Manufacturer Item Number	NU320G1C3
Weight / LBS	17.945
Bore	3.937 Inch 100 Millimeter
Outside Diameter	8.465 Inch 215 Millimeter
Width	1.85 Inch 47 Millimeter
bore diameter:	100 mm
static load capacity:	335000 N
outside diameter:	215 mm
precision rating:	ISO Class 0
overall width:	47 mm
maximum rpm:	3800 rpm
flanges:	(2) Outer Ring
bearing material:	Hardened Alloy Steel
bore type:	Straight
cage material:	High Strength Machined Brass Rivetless w/ square holes
number of rows:	1
finish/coating:	Uncoated
internal clearance:	C3
closure type:	Open
ring separation:	Separable Inner Ring
fillet radius:	2.5 mm

operating temperature range:	-40 to 120 °C
manufacturer product page:	Click here
dynamic load capacity:	299000 N