

# INA NKI40/30-TN-XL needle roller bearings

YOU'LL FIND AN EXTENSIVE 80.963x160x40 Size (mm) SELECTION OF INA NKI40/30-TN-XL needle roller bearings FOR SALE.

|                     |  |
|---------------------|--|
| Size (mm)           | 80.963x160x40  |
| Bore Diameter (mm)  | 80,963   |
| Outer Diameter (mm) | 160  |
| Width (mm)          | 40   |
| d                   | 3 3/16 inch  |
| D                   | 160 mm   |
| C                   | 40 mm  |
| B                   | 70 mm  |
| rmin                | 2 mm   |
| m                   | 4,27 kg / Weight   |
| Cr                  | 212000 N / Dynamic load rating (radial)                                |
| e                   | 0,22   |
| Y1                  | 3,14   |
| Y2                  | 4,67   |
| C0r                 | 270000 N / Static load rating (radial)                                 |
| Y0                  | 3,07   |
| nG                  | 2160 1/min / Limiting speed  |
| Cur                 | 25500 N / Fatigue limit load, radial                                   |
| Fa max              | 7600 N / Permissible axial load, for inner ring without axial abutment |
| Mi                  | 14 Nm / Tightening torque per clamping screw                           |

|           |   |
|-----------|---|
| Ma        | 9 Nm / Tightening torque per clamping screw |
| SNW18.303 | Designation, adapter sleeve, US design      |
| SNV160    | Designation, plummer block housing          |