

# INA NN3060-AS-K-M-SP cylindrical roller bearings

How do I place an EMERGENCY order for a INA NN3060-AS-K-M-SP cylindrical roller bearings Double Row Configuration that I Cylindrical Bore Bore Type want to pick up at a our store?

|                         |                      |
|-------------------------|----------------------|
| Bore Type               | Cylindrical Bore     |
| Enclosure               | Open                 |
| Configuration           | Double Row           |
| Roller Profile          | Symmetric            |
| Center Guidance         | Fixed Inner Ring Rib |
| Retainer Material       | Machined Brass       |
| Nr. of Holes            | 8                    |
| Weight                  | 584.000 kg           |
| d                       | 500 mm               |
| D                       | 830 mm               |
| B                       | 264 mm               |
| Fillet Radius/Chamfer   | 7.5 mm               |
| Groove Width A          | 45 mm                |
| Hole Diameter (do)      | 20 mm                |
| Dynamic Load Rating     | 9,300,000 N          |
| Static Load Rating      | 13,000,000 N         |
| Limiting Speed – Grease | 420 rpm              |
| Limiting Speed – Oil    | 540 rpm              |
| Constant e              | 0.32                 |
| Axial Load Factor Y0    | 2.04                 |
| Axial Load Factor Y1    | 2.09                 |
| Axial Load Factor Y2    | 3.11                 |

|                  |                   |
|------------------|-------------------|
| Radial Clearance | 0.260 to 0.410 mm |
| da (min)         | 536 mm            |
| Da (max)         | 794 mm            |
| ra (max)         | 6 mm              |