

INA PAKY1 bearing units

Our highly-skilled and factory-trained service experts have the resources to help you with all your INA PAKY1 bearing units needs 35x62x19.9 Size (mm) – including routine maintenance, major repairs, warranty service, and equipment inspections.

Size (mm)	35x62x19.9
Bore Diameter (mm)	35
Outer Diameter (mm)	62
Width (mm)	19,9
d	35 mm
D	62 mm
T	19,9 mm
d1	62 mm
r min.	1 mm
A	24 mm
D1	37 mm
R	50 mm
da min.	51 mm
Da max.	46 mm
ra max.	1 mm
Weight	0,231 Kg
Basic dynamic load rating (C)	39,5 kN
Basic static load rating (C0)	78 kN
(Grease) Lubrication Speed	3000 r/min
Inventory	0.0
Manufacturer Name	NSK
Minimum Buy Quantity	N/A

Weight / Kilogram	0.28
EAN	0029176029530
Product Group	B00308
Rolling Element	Ball Bearing
Thrust Bearing	Yes
Single or Double Direction	Single Direction
Banded	No
Cage Material	Steel
Precision Class	Non-Precision
Component Description	Roller Assembly Plus Raceways
Other Features	Single Row With Aligning Seat
Long Description	35MM Bore 1; 37MM Bore 2; 62MM Outside Diameter; 20MM Height; Ball Bearing; Single Direction; Not Ba
Inch – Metric	Metric
UNSPSC	31171552
Harmonized Tariff Code	8482.10.50.08
Noun	Bearing
Keyword String	Ball Thrust
Manufacturer Item Number	53207
Weight / LBS	0.50927
Bore 1	1.378 Inch 35 Millimeter
Overall Height with Aligning Washer	0 Inch 0 Millimeter
Bore 2	1.457 Inch 37 Millimeter
Height	0.787 Inch 20 Millimeter
Outside Diameter	2.441 Inch 62 Millimeter
bore diameter:	35 mm

static load capacity:	17600 lbf
outside diameter:	62 mm
dynamic load capacity:	8900 lbf
overall width:	22 mm
operating temperature range:	Maximum of +120 °C
thrust bearing type:	Single-Direction
maximum rpm:	4500 rpm
outside diameter design:	Straight
cage material:	Steel Cage
separable or banded:	Separable
fillet radius:	1 mm
race type:	Flat
series:	52300
precision rating:	ABEC1, P0
SRI	5.15
hidYobi	53207
LangID	1
D_	62
SREX	0.04
C	39.5
B_	19.9
hidTable	ecat_NSSDTB
Oil rpm	4500
SRE	5.15
mass	0.231
GRS rpm	3000
ra	1
SRIX	0.04
D_a	46

SRIN	0
C0	78
SREN	0
D_1	37
Prod_Type3	TB_SD_WAS
da	51
DA_	9.525
Z_	14
yobi	53207
A_	24
T3	19.9
SDM_	48.5
r	1
KBRG	5121
R_	50