

# INA PASE5/8 bearing units

Request A Quote For Your Special INA PASE5/8 bearing units Needs Today! Free Quotes. ISO 9001 certified. 85 mm d

d	85 mm
D	130 mm
B	22 mm
rs min	1.1 mm
Radial clearance class	CN
Mass	0.89 kg
Dynamic load, C	49.5 kN
Static load, C0	43 kN
Fatigue limit load, Cu	1.89 kN
f0	15.8
Nlim (grease)	2,400 rpm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	80 °C
Characteristic cage frequency, FTF	0.44 Hz
Characteristic rolling element frequency, BSF	7.84 Hz
Characteristic outer ring frequency, BPF0	6.56 Hz
Characteristic inner ring frequency, BRFI	8.44 Hz
da min	91.5 mm
da max	97 mm
Da max	123.5 mm
ra max	1 mm

Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.905
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	85MM Bore; 130MM Outside Diameter; 22MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1   ISO P0; No
Other Features	Deep Groove   Double Lip Friction Nitrile Rubber Seal   -20 To 120 Deg C   Prelubricated
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	1.96
Bore	3.346 Inch   85 Millimeter

Outside Diameter	5.118 Inch   130 Millimeter
Inner Race Width	0 Inch   0 Millimeter
Outer Race Width	0.866 Inch   22 Millimeter