

INA RA25 bearing units

INA RA25 bearing units Warehouse offers car parts and car accessories. We sell 269.999 mm Da discount 131.762 mm da online as well as cheap machinery parts.

da	131.762 mm
Da	269.999 mm
Ca	105.816 mm
A1	158.75 mm
A2	215.9 mm
S	4.763 mm
ba	77.787 mm
H	317.5 mm
H1	160.35 mm
H2	63.5 mm
J min.	431.8 mm
J max.	463.55 mm
J1	95.25 mm
L	539.75 mm
N1	28.575 mm
R1	95.25 mm
R2	39.688 mm
RG	3/8 NPT
PG	1/4 NPT
h	50.8 mm
Housing	SAW 530
Bearing	23230 CCK/W33
Adapter sleeve assembly	SNW 130×5.3/16

Stabilizing ring	SR-30-0
Labyrinth ring	2 x LOR 125
End plug (suffix Y)	EPR 16
Bearing limiting speed	2200 r/min
P60°	230 kN
P90°	138 kN
P120°	87.2 kN
P150°	80.1 kN
P180°	96.1 kN
Pa	43.2 kN
Mass pillow block	92.5 kg
Cap bolt	4 x 3/4-10 UNC
Cap bolt recommended tightening torque	359.3 N·m
Cap bolt, SAE grade	5
Eye bolt	2 x 3/8-16 UNC
Appropriate attachment bolt size G	1 in
Initial grease fill	623.7 g