

# INA RATY20 bearing units

We work closely with our INA RATY20 bearing units manufacturing partners to bring the best 6 RoHS value to Quote Days to Ship customers.

|                                     |               |
|-------------------------------------|---------------|
| Days to Ship                        | Quote         |
| RoHS                                | 6             |
| Inner/Outer Ring Material           | [Steel] Steel |
| Bearing Style                       | Open Type     |
| Outer Ring Shape                    | Flat          |
| Precision                           | Grade 0       |
| I.D.(Ø)                             | 110           |
| O.D.(Ø)                             | 170           |
| Width(mm)                           | 28            |
| Basic Dynamic Load Rating(N)        | 85000         |
| Max. Allowed rpm(rpm)               | 3800          |
| Rolling Element Material            | [Steel] Steel |
| Retainer Type                       | Punching      |
| Basic Load Rating, Static Rating(N) | 73000         |
| Clearance sign                      | CM            |
| Accuracy(Class)                     | Class 0       |
| Acoustic Symbol                     | No            |
| Holder Symbol                       | No            |
| Symbol of Bearing Ring Shape        | No            |
| Seal, Shield Symbols                | No            |
| Precision Grade Symbol              | No            |
| Special Configurations Code         | No            |
| Rubugado Symbol                     | No            |

|                             |                 |
|-----------------------------|-----------------|
| Material Symbol             | No              |
| Spacer, Sleeve symbol       | No              |
| Types                       | No              |
| Type                        | Ball            |
| Specifications, Environment | Standard        |
| Load Direction              | Radial          |
| Outer Ring                  | With Outer Ring |
| Number of Raceway Ring Rows | Single Row      |
| Size Standards              | Metric System   |
| Combination symbol          | No              |
| Low Torque Specification    | No              |
| Internal Symbol             | No              |
| Torque Symbol               | No              |
| d                           | 110             |
| D                           | 170             |
| B                           | 28              |
| Specifications/Environment  | Standard        |
| Preload Mark                | CM              |