

# INA RFE45 bearing units

Can't find what you're looking for INA RFE45 bearing units ? Our expert 110x200x38 Size (mm) Representatives be in contact with 200 Outer Diameter (mm) you shortly!

Size (mm)	110x200x38
Bore Diameter (mm)	110
Outer Diameter (mm)	200
Width (mm)	38
d	110 mm
D	200 mm
B	38 mm
C	38 mm
rn	0,5 mm
r min.	2,1 mm
da min.	121 mm
da max	132 mm
Da max.	189 mm
ra max.	2 mm
Weight	4,36 Kg
Basic dynamic load rating (C)	144 kN
Basic static load rating (C0)	117 kN
(Grease) Lubrication Speed	3 200 r/min
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	4547359570694

Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1   ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	110MM Bore; 200MM Outside Diameter; 38MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1   I
Other Features	Deep Groove   Shell Alvania Prelubricated
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	8.5098
Inner Race Width	0 Inch   0 Millimeter
Outer Race Width	1.496 Inch   38 Millimeter
Outside Diameter	7.874 Inch   200 Millimeter
Bore	4.331 Inch   110 Millimeter
bore diameter:	110 mm
precision rating:	ISO Class 0
outside diameter:	200 mm
finish/coating:	Uncoated
overall width:	38 mm

bearing material:	High Carbon Chrome Steel
bore type:	Round
cage material:	Steel
closure type:	Double Shielded
inner ring width:	38 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	38 mm
snap ring included:	Without Snap Ring
maximum rpm (grease):	3200 rpm
internal clearance:	CN
fillet radius:	2.1 mm
operating temperature range:	-40 to 120 °C
maximum rpm:	3800 RPM
dynamic load capacity:	144000 N
series:	62
static load capacity:	117000 N
manufacturer product page:	<a href="#">Click here</a>