INA RHE20 bearing units

170 FSNT 512-610 Housing Million used INA RHE20 bearing units instantly searchable. SR110X10 Locating Rings (width x 0D) Shop our large selection of parts 22212K Bearing based on brand, price, description, and location. Order the with stock \dots

Housing PSNT 512-610 Bearing 22212K Locating Rings (width x OD) SR110X10 Seal TA512 Seal Type Taconite Adapter Sleevel H312 Locknut KM12 Lockwasher MB12 End Cover2 EC512-610 Material Cast Iron Housing Mass 5.30 Kg Bolt Qty 4 Cage Type EJ C1 Dynamic Load Rating 169 C0 Static Load Rating 174 Max Oil Speed 5500 Max Grease Speed 4400 Shaft Diameter d 55 mm A 105.00 mm A1 70 mm A3 G M12		
Locating Rings (width x OD) SR110X10 Seal Type Taconite Adapter Sleevel H312 Locknut KM12 Lockwasher MB12 End Cover2 EC512-610 Material Cast Iron Housing Mass 5.30 Kg Bolt Qty 4 Cage Type EJ C1 Dynamic Load Rating 169 C0 Static Load Rating 174 Max Oil Speed 5500 Max Grease Speed 4400 Shaft Diameter d 55 mm A 105.00 mm A1 70 mm A3 165 mm	Housing	FSNT 512-610
Seal TA512 Seal Type Taconite Adapter Sleevel H312 Locknut KM12 Lockwasher MB12 End Cover2 EC512-610 Material Cast Iron Housing Mass 5.30 Kg Bolt Qty 4 Cage Type EJ C1 Dynamic Load Rating 169 C0 Static Load Rating 174 Max Oil Speed 5500 Max Grease Speed 4400 Shaft Diameter d 55 mm A 105.00 mm A1 70 mm A3 165 mm	Bearing	22212K
Seal Type Taconite Adapter Sleevel H312 Locknut KM12 Lockwasher MB12 End Cover2 EC512-610 Material Cast Iron Housing Mass 5.30 Kg Bolt Qty 4 Cage Type EJ C1 Dynamic Load Rating 169 C0 Static Load Rating 174 Max Oil Speed 5500 Max Grease Speed 4400 Shaft Diameter d 55 mm A 105.00 mm A1 70 mm A3 165 mm	Locating Rings (width x OD)	SR110X10
Adapter Sleevel H312 Locknut KM12 Lockwasher MB12 End Cover2 EC512-610 Material Cast Iron Housing Mass 5.30 Kg Bolt Qty 4 Cage Type EJ C1 Dynamic Load Rating 169 C0 Static Load Rating 174 Max Oil Speed 5500 Max Grease Speed 4400 Shaft Diameter d 55 mm A 105.00 mm A1 70 mm A3 165 mm	Seal	TA512
Locknut KM12 Lockwasher MB12 End Cover2 EC512-610 Material Cast Iron Housing Mass 5.30 Kg Bolt Qty 4 Cage Type EJ C1 Dynamic Load Rating 169 C0 Static Load Rating 174 Max Oil Speed 5500 Max Grease Speed 4400 Shaft Diameter d 55 mm A 105.00 mm A1 70 mm A3 165 mm	Seal Type	Taconite
Lockwasher End Cover2 EC512-610 Material Cast Iron Housing Mass 5.30 Kg Bolt Qty 4 Cage Type EJ C1 Dynamic Load Rating C0 Static Load Rating MB12 Example 170 Example 170 Max Oil Speed Max Grease Speed Au Au Au Au Au Au Au Au Au A	Adapter Sleeve1	H312
End Cover2 Material Cast Iron Housing Mass 5.30 Kg Bolt Qty 4 Cage Type EJ C1 Dynamic Load Rating C0 Static Load Rating Max Oil Speed Max Grease Speed A 105.00 mm A1 A3 165 mm	Locknut	KM12
Material Cast Iron Housing Mass 5.30 Kg Bolt Qty 4 Cage Type EJ C1 Dynamic Load Rating 169 C0 Static Load Rating 174 Max Oil Speed 5500 Max Grease Speed 4400 Shaft Diameter d 55 mm A 105.00 mm A1 70 mm A3 165 mm	Lockwasher	MB12
Housing Mass Bolt Qty Cage Type C1 Dynamic Load Rating C0 Static Load Rating Max Oil Speed Max Grease Speed Shaft Diameter d A 105.00 mm A1 A3 165 mm	End Cover2	EC512-610
Bolt Qty Cage Type EJ C1 Dynamic Load Rating C0 Static Load Rating Max Oil Speed Max Grease Speed Shaft Diameter d A 105.00 mm A1 A3 165 mm	Material	Cast Iron
Cage Type EJ C1 Dynamic Load Rating C0 Static Load Rating Max Oil Speed Max Grease Speed Shaft Diameter d A 105.00 mm A1 A3 165 mm	Housing Mass	5.30 Kg
C1 Dynamic Load Rating 169 C0 Static Load Rating 174 Max Oil Speed 5500 Max Grease Speed 4400 Shaft Diameter d 55 mm A 105.00 mm A1 70 mm A3 165 mm	Bolt Qty	4
C0 Static Load Rating 174 Max Oil Speed 5500 Max Grease Speed 4400 Shaft Diameter d 55 mm A 105.00 mm A1 70 mm A3 165 mm	Cage Type	EJ
Max Oil Speed 5500 Max Grease Speed 4400 Shaft Diameter d 55 mm A 105.00 mm A1 70 mm A3 165 mm	C1 Dynamic Load Rating	169
Max Grease Speed 4400 Shaft Diameter d 55 mm A 105.00 mm A1 70 mm A3 165 mm	CO Static Load Rating	174
Shaft Diameter d 55 mm A 105.00 mm A1 70 mm A3 165 mm	Max Oil Speed	5500
A 105.00 mm A1 70 mm A3 165 mm	Max Grease Speed	4400
A1 70 mm A3 165 mm	Shaft Diameter d	55 mm
A3 165 mm	Α	105.00 mm
	A1	70 mm
G M12	A3	165 mm
	G	M12

Н	134 mm
H1	70.0 mm
H2	30 mm
J	210.00 mm
J1	35 mm
J2	234 mm
L	255 mm
N	15 mm
N1	20.00 mm
UPC Code	99999999