

INA RHE50 bearing units

Browse 60 mm d INA RHE50 bearing units Categories in the Manufacturers Online Free. including .

d	60 mm
D	95 mm
B	18 mm
rs min	1.1 mm
Radial clearance class	C3
Mass	0.41 kg
Dynamic load, C	29.5 kN
Static load, C0	23.2 kN
Fatigue limit load, Cu	1.05 kN
f0	15.6
Nlim (oil)	8,300 rpm
Nlim (grease)	7,000 rpm
Min operating temperature, Tmin	-60 °C
Characteristic cage frequency, FTF	0.43 Hz
Characteristic rolling element frequency, BSF	7.38 Hz
Characteristic outer ring frequency, BPF0	6.07 Hz
Characteristic inner ring frequency, BRFI	7.93 Hz
da min	66.5 mm
Da max	88.5 mm
ra max	1 mm
Inventory	0.0

Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.49
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Brass
Internal Clearance	C3-Loose
Inch – Metric	Metric
Long Description	60MM Bore; 95MM Outside Diameter; 18MM Outer Race Width; Open; Ball Bearing; ABEC 1 ISO P0; No Fil
Other Features	Deep Groove Riveted Solid Cage
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	0.90609
Bore	2.362 Inch 60 Millimeter
Outside Diameter	3.74 Inch 95 Millimeter
Inner Race Width	0 Inch 0 Millimeter
Outer Race Width	0.709 Inch 18 Millimeter