

INA RRY12-VA bearing units

INA RRY12-VA bearing units, Units and Housings CAD models , Manufacturing Service . Get Your 8 Days or more Days to Ship Free.

Days to Ship	8 Days or more
RoHS	6
Inner/Outer Ring Material	[Steel] Steel
Bearing Style	Rubber Sealed
Outer Ring Shape	Flat
Precision	Grade 0
I.D.(Ø)	80
O.D.(Ø)	140
Width(mm)	26
Basic Dynamic Load Rating(N)	72500
Max. Allowed rpm(rpm)	4500
Rolling Element Material	[Steel] Steel
Retainer Type	Punching
Basic Load Rating, Static Rating(N)	53000
Clearance sign	CM
Accuracy(Class)	Class 0
Acoustic Symbol	No
Grease Type	AS2S1
Holder Symbol	No
Symbol of Bearing Ring Shape	No
Seal, Shield Symbols	VV
Precision Grade Symbol	No
Special Configurations Code	No

Rubugado Symbol	No
Material Symbol	No
Spacer, Sleeve symbol	No
Types	No
Type	Ball
Specifications, Environment	Standard
Load Direction	Radial
Outer Ring	With Outer Ring
Number of Raceway Ring Rows	Single Row
Size Standards	Metric System
Combination symbol	No
Low Torque Specification	No
Internal Symbol	No
Torque Symbol	No