

INA RSA060 bearing units

25 mm d offers a INA RSA060 bearing units selection of Genuine at Wholesale Prices. We are a 47 mm D INA RSA060 bearing units Certified Parts Retailer 12 mm B

d	25 mm
D	47 mm
B	12 mm
a min	1.9 mm
a max	2.06 mm
Ca min	3.02 mm
Ca max	3.18 mm
rs min	0.6 mm
rNs min	0.5 mm
D3 max	44.6 mm
b min	1.35 mm
b max	1.65 mm
r0 max	0.4 mm
D4 max	52.7 mm
f	1.12 mm
Snap ring reference	R47
Radial clearance class	CN
Mass	0.08 kg
Dynamic load, C	10.1 kN
Static load, C0	5.85 kN
Fatigue limit load, Cu	0.27 kN
f0	14.5
Nlim (grease)	15,000 rpm

Min operating temperature, T_{min}	-20 °C
Max operating temperature, T_{max}	120 °C
Characteristic cage frequency, FTF	0.41 Hz
Characteristic rolling element frequency, BSF	5.49 Hz
Characteristic outer ring frequency, BPF0	4.12 Hz
Characteristic inner ring frequency, BRFI	5.88 Hz
d_a min	29 mm
D_a max	43 mm
r_a max	0.6 mm
r_{Na} max	0.5 mm
D_b min	53.5 mm