

# INA RSL183026-A cylindrical roller bearings

170 Million used INA RSL183026-A cylindrical roller bearings instantly searchable. Shop our large selection of parts 17 mm d based on brand, price, description, 35 mm D and location. Order the 10 mm B with stock ...

d	17 mm
D	35 mm
B	10 mm
rs min	0.3 mm
Radial clearance class	C3
Mass	0.04 kg
Dynamic load, C	6.8 kN
Static load, C0	3.35 kN
Fatigue limit load, Cu	0.15 kN
f0	13.6
Nlim (grease)	14,000 rpm
Min operating temperature, Tmin	-25 °C
Characteristic cage frequency, FTF	0.39 Hz
Characteristic rolling element frequency, BSF	4.47 Hz
Characteristic outer ring frequency, BPF0	3.14 Hz
Characteristic inner ring frequency, BPFI	4.86 Hz
da min	19 mm
da max	21 mm
Da max	33 mm

ra max	0.3 mm
bore diameter:	17 mm
precision rating:	ISO Class 0
outside diameter:	35 mm
finish/coating:	Uncoated
overall width:	10 mm
bearing material:	High Carbon Chrome Steel
bore type:	Round
cage material:	Steel
closure type:	Single Seal
inner ring width:	10 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	10 mm
snap ring included:	Without Snap Ring
maximum rpm (grease):	14000 rpm
internal clearance:	C3
fillet radius:	0.3 mm
operating temperature range:	-40 to 120 °C
maximum rpm:	24000 RPM
dynamic load capacity:	6800 N
series:	60
static load capacity:	3350 N
manufacturer product page:	<a href="#">Click here</a>