

ISB 2212 KTN9+H312 self aligning ball bearings

ISB 2212 KTN9+H312 self aligning ball bearings Industries and 9.0 Inventory Applications ? We sell discount online as well as cheap machinery parts. N/A Minimum Buy Quantity

| | |
|---------------------------|---|
| Inventory | 9.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight | 0.851 |
| EAN | 7316576652110 |
| Product Group | B04311 |
| Internal Clearance | C3-Loose |
| Mounting Method | Shaft Mount |
| Rolling Element | Spherical Roller Bearing |
| Bore Profile | Straight |
| Cage Material | Steel |
| Enclosure | Open |
| Number of Rows of Rollers | Double Row |
| Relubricatable | Yes |
| Withdrawal Sleeve | Not Applicable |
| Withdrawal Nut | Not Applicable |
| Inch – Metric | Metric |
| Long Description | 55MM Straight Bore; 100MM Outside Diameter; 25MM Width; C3-Loose Clearance; Shaft Mount; Double Row |
| UNSPSC | 31171510 |
| Harmonized Tariff Code | 84823080 |

| | |
|------------------------------|---|
| Noun | Bearing |
| Keyword String | Spherical |
| Weight / LBS | 1.875 |
| B | 0.984 Inch 25 Millimeter |
| d | 2.165 Inch 55 Millimeter |
| D | 3.937 Inch 100 Millimeter |
| Adapter Part Number | Not Applicable Inch Not Applicable Millimeter |
| bore diameter: | 55 mm |
| maximum rpm: | 8500 RPM |
| outside diameter: | 100 mm |
| operating temperature range: | Maximum of +390 °F |
| overall width: | 25 mm |
| cage material: | Steel |
| bore type: | Straight |
| bearing material: | Steel |
| outer ring type: | Not Split |
| cage type: | Inner Ring Guided |
| internal clearance: | C3 |
| precision rating: | Not Rated |
| closure type: | Open |
| finish/coating: | Uncoated |
| lubrication hole type: | Lubrication Groove & Hole |
| outer ring width: | 25 mm |
| dynamic load capacity: | 125 kN |
| fillet radius: | 1.5 mm |
| static load capacity: | 127 kN |
| series: | 222 |