

ISB 22244 spherical roller bearings

ISB 22244 spherical roller bearings with easy-to-use parts graphics, 62.789 mm Ca giving you 200 mm Da the ability to check parts availability, pricing, examine 109.537 mm da remanufactured options.

da	109.537 mm
Da	200 mm
Ca	62.789 mm
A1	120.65 mm
A2	234.95 mm
ba	51.594 mm
H	239.713 mm
H1	125.425 mm
H2	50.8 mm
J min.	320.675 mm
J max.	368.3 mm
J1	69.85 mm
L	419.1 mm
N1	22.225 mm
R1	67.945 mm
R2	31.75 mm
RG	3/8 NPT
PG	1/4 NPT
h	42.862 mm
Housing	SAF 026 KA
Bearing	23026 CCK/W33

Adapter sleeve assembly	SNW 3026×4.5/16
Stabilizing ring	2 x 38151-26
Taconite seal	TER 115
End plug (suffix Y)	EPR 15
Max. speed for Taconite seal	700 r/min
P60°	149 kN
P90°	89 kN
P120°	55.6 kN
P150°	50.7 kN
P180°	60.9 kN
Pa	20.2 kN
Mass pillow block	32.2 kg
Cap bolt	2 x 3/4-10 UNC
Cap bolt recommended tightening torque	203.4 N·m
Cap bolt, SAE grade	5
Appropriate attachment bolt size G	0.75 in
Initial grease fill	232.47 g