

ISB 230/1060 EKW33+A0H30/1060 spherical roller bearings

Find the discount ISB 230/1060 EKW33+A0H30/1060 spherical roller bearings online 15.0 Inventory you need . We offer ... If you check out our large selection of ISB 230/1060 EKW33+A0H30/1060 spherical roller bearings once .

| | |
|---------------------------|--|
| Inventory | 15.0 |
| Manufacturer Name | TIMKEN |
| Minimum Buy Quantity | N/A |
| Weight | 27 lb |
| EAN | 0053893534510 |
| Product Group | M06288 |
| Number of Mounting Holes | 4 |
| Mounting Method | Concentric Collar |
| Housing Style | 4 Bolt Square Flange Block |
| Rolling Element | Tapered Roller Bearing |
| Housing Material | Cast Iron |
| Expansion / Non-expansion | Non-expansion |
| Mounting Bolts | 3/4 Inch |
| Relubricatable | Yes |
| Seals | Double Lip Radial |
| Housing Configuration | 1 Piece Solid |
| Pilot Configuration | No Pilot |
| Inch – Metric | Inch |
| Long Description | 4 Bolt Square Flange Block; 2-15/16" Bore; 8-1/2" Bolt Circle; 6" Bolt Spacing; 1 Pie |

| | |
|---------------------------------------|--|
| Other Features | Double Row Wide Inner Race With Set Screw |
| UNSPSC | 31171501 |
| Harmonized Tariff Code | 8483.20.40.80 |
| Noun | Bearing |
| Keyword String | Flanged |
| Manufacturer Item Number | E-4BF-TRB-2 15/16 |
| Weight / LBS | 27 |
| Nominal Bolt Circle Diameter Round | 8.5 Inch 215 Millimeter |
| Cartridge Pilot Depth | 0 Inch 0 Millimeter |
| D | 4.5 Inch 114.3 Millimeter |
| Cartridge Pilot Diameter | 0 Inch 0 Millimeter |
| d | 2.938 Inch 74.625 Millimeter |
| Bolt Spacing | 6 Inch 152.4 Millimeter |
| Shaft Size | 2.9375 in |
| Shaft Size Type | Imperial |
| UPC Code | 053893534510 |
| Dimension B | 4-1/2 in |
| Dimension L | 7-3/4 in |
| Dimension A | 3-15/16 in |
| Dimension J | 6 in |
| Dimension A2 | 3/16 in |
| Bolt Diameter | 3/4 in |
| Dimension A1 | 1-5/8 in |
| Dimension D 1 | 6 in |
| Dimension d1 | 4-23/32 in |
| e | 0.46 |
| X (if $F_a/F_r \leq e$) | 0.87 |

| | |
|--|---|
| Y (if $F_a/F_r \leq e$) | 1.87 |
| X (if $F_a/F_r > e$) | 0.7 |
| Y (if $F_a/F_r > e$) | 2.26 |
| K Factor | 1.30 |
| C90 Dynamic Load Rating ² | 12300 lb |
| C0 Static Load Rating | 61200 lb |
| Fa-max Maximum Permissible Thrust Load ³ | 5181 lb |
| Fr-max Maximum Allowable Slip Fit Radial Load ⁴ | 10000 lb |
| Max. Speed ⁵ | 2060 rpm |
| Note | Note: All units have a 1/8 pipe thread grease fitting The Maximum Permissible Thrust Load applies to |